

HIKVISION

لیست قیمت رسمی مهر ۱۳۹۷

درباره هایک ویژن

شرکت هایک ویژن (Hikvision) یک شرکت چینی فعال در زمینه تولید تجهیزات مداربسته است. این شرکت کار خود را در سال ۲۰۰۱ در شهر هانگ ژو آغاز کرد و مسیر پیشرفت را با سرعتی بالا طی کرد به طوری که در سال ۲۰۱۴ به عنوان سومین تولید کننده بزرگ تجهیزات حفاظتی - امنیتی و اولین تولید کننده تجهیزات مداربسته در جهان شناخته شد. شرکت هایک ویژن در سال ۲۰۱۳ بیش از ۱۳۰۰۰ نفر را به صورت مستقیم به اشتغال در آورده که با داشتن تیم تحقیق و توسعه ای ۴۰۰۰ نفری دارای بزرگترین تیم تحقیق و توسعه جهان محسوب می شود. این شرکت دارای ۳۰ نماینده مملی در چین و بیش از ۱۶ نماینده بین المللی در جهان است که تجهیزات این شرکت را به طور فعال توزیع می کنند.

آسان تجارت

نمایندگی پخش محصولات هایک ویژن



Asan Tejarat

افتخارات هایک ویژن

سومین تولید کننده بزرگ تجهیزات حفاظتی جهان
در سال ۲۰۱۴ و ۲۰۱۵
اولین تولید کننده دوربین مداربسته و تجهیزات
نظارت تصویری در سال ۲۰۱۵
تولید بیشتر ۲۰٪ از کل دستگاه های DVR دنیا
برنده جایزه ملی ZUBR روسیه در سال ۲۰۱۳
برنده جایزه طراحی محصول RED DOT در سال
۲۰۱۲
برنده جایزه طراحی بهترین دوربین IP در Secutech
در سال ۲۰۱۲
برنده جایزه "Golden Excellence Award" در
سال ۲۰۱۱ CPSE
برنده جایزه FSdays در سال ۲۰۱۰

برای کنترل موجودی در لیست با
شماره های زیر تماس بگیرید:

021-88769732

021-88171031

021-88512942

	1	2	3	4	5	6
Click for More information	DS-2CD2120F-I	DS-2CD2120F-IS	DS-2CD2142FWD-I	DS-2CD2142FWD-IS	DS-2CD2152F-IS	DS-2CD1143G0-I



Price (Rials)	۱۲,۶۳۰,۰۰۰	۱۲,۶۳۰,۰۰۰	Call:88512912	۱۹,۲۹۰,۰۰۰	۲۳,۸۹۰,۰۰۰	۱۴,۰۰۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP (2560x1920/20fps)	4MP (2688x1520/20fps)	5MP (2560x1920/20fps)	4MP (2688x1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.028Lux @ F2
Lens	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8/4/6mm Fix
Viewing Angle	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°/51
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP67 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	No
Microphone Support	No	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	No
WDR	DWDR	DWDR	Yes (120db)	Yes (120db)	DWDR	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC

	13	14	15	16	17	18
Click for More information	DS-2CD2510F	DS-2CD2520F	DS-2CD2522FWD-I	DS-2CD2542FWD-IS	DS-2CD2720F-I	DS-2CD2720F-IS



Price (Rials)	Call:88512912	Call:88512912	Call:88512912	۲۲,۷۰۰,۰۰۰	۲۲,۵۳۰,۰۰۰	Call:88512912
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	5MP (2560x1920/20fps)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8-12mm Varifocal	2.8-12mm Varifocal
Viewing Angle	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 10m	Up to 10m	Up to 10m	Up to 10m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	No	No	No	1.ch Audio Input	No	1.ch Audio Input
WDR	DWDR	DWDR	Yes (120db)	Yes (120db)	DWDR	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

19

20

21

22

23

24

Click for More information

DS-2CD2720F-IZ

DS-2CD2720F-IZS

DS-2CD2722FWD-IZ

DS-2CD2732F-IZ

DS-2CD2742FWD-IZ

DS-2CD2742FWD-IZS



Price (Rials)	Call:88512912	Call:88512912	Call:88512912	Call:88512912	۳۴,۸۱۰,۰۰۰	Call:88512912
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	3MP (2048x1536/20FPS)	4MP (2688x1520/20fps)	4MP (2688x1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	No	1ch. Audio Input	1ch. Audio Input	No	1ch. Audio Input	1ch. Audio Input
WDR	DWDR	DWDR	Yes (120db)	DWDR	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

25

26

27

Click for More information

DS-2CD2752F-IS

DS-2CD2752F-IZS

DS-2CD1743G0-I



Price (Rials)	۴۰,۹۵۰,۰۰۰	Call:88512912	۲۳,۸۹۰,۰۰۰
Camera Type	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	5MP (2560×1920/20fps)	5MP (2560×1920/20fps)	2MP (1920x1080/25FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.018Lux @ F2
Lens	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP67
SD Card Support	Yes	Yes	Yes
Microphone Support	1ch. Audio Input	1ch. Audio Input	No
WDR	DWDR	DWDR	Yes (120db)
WIFI	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Motion detection, Tamper Detection

برای کنترل موجودی در لیست با
شماره های زیر تماس بگیرید:

021-88769732

021-88171031

021-88512942

	28	29	30	31	32	33
Click for More information	DS-2CD2E20F-W	DS-2CD2Q10FD-IW	DS-2CV2Q21FD-IW/32GB-T	DS-2CV2U21FD-IW/32GB-T	DS-2CD2F22WD-IS	DS-2CD2F42WD-IS
						
Price (Rials)	Call:88512912	Call:88512912	۱۶,۰۵۰,۰۰۰	۱۲,۶۳۰,۰۰۰	Call:88512912	Call:88512912
Camera Type	Roof mount Dome	Indoor Pan-tilt	Indoor Pan-tilt		Pan-Tilt Dome	Pan-Tilt Dome
Imaging Sensor	1/3" Prog. CMOS	1/4" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	1MP (1280x720/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP (2688x1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8mm / 4mm Fix	2.8mm / 4mm Fix	2.8mm Fix	2.8mm Fix	4mm Fix	4mm Fix
Viewing Angle	98.5° / 79°	98.5° / 79°	98.5°	98.5°	79°	79°
IR Range	-	Up to 10m	Up to 10m	Up to 10m	Up to 10m	Up to 10m
Body Type & Standard	Metal / IP66 & IK10	Plastic	Plastic	Plastic	Metal	Metal
SD Card Support	No	Yes (up to 64GB)	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 64GB)	Yes (up to 64GB)
Microphone Support	No	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	1ch. Audio Input	1ch. Audio Input
WDR	DWDR	DWDR	WDR	NO	Yes (120db)	Yes (120db)
WIFI	Yes	Yes	Yes	Yes	No	No
Power Supply	12V DC	12V DC or POE	12V DC or POE	12V DC	12V DC	12V DC
Other Features	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI,Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI,Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI,Detection

	34	35	36	37	38	39
Click for More information	DS-2CD2F52F-IS	DS-2CD2420F-IW	DS-2CD2422FWD-IW	DS-2CD2442FWD-IW	DS-2CD2D14WD	DS-2CD2942F-IS



Price (Rials)	۲۶,۸۵۰,۰۰۰	۱۲,۶۳۰,۰۰۰	Call:88512912	۱۷,۴۱۰,۰۰۰	۱۳,۰۶۰,۰۰۰	Call:88512912
Camera Type	Pan-Tilt Dome	Cube	Cube	Cube	Miniature	FishEye
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/4" Prog. CMOS	1/3" Prog. CMOS
Resolution	5Mp(2560×1920/20fps)	2MP(1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP (2688×1520/20fps)	1MP (1280x720/25FPS)	4MP (2464x1520/12FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F1.2
Lens	4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	3.6mm Fix	1.6mm Fix
Viewing Angle	79°	98.5°/79°	98.5°/79°	98.5°/79°	65°	186° Panoramic
IR Range	Up to 10m	Up to 10m	Up to 10m	Up to 10m	-	Up to 10m
Body Type & Standard	Metal	Plastic	Plastic	Plastic	Metal	Plastic
SD Card Support	-	Yes (up to 64GB)	Yes (up to 64GB)	Yes (up to 64GB)	No	Yes (up to 64GB)
Microphone Support	1ch. Audio Input	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	No	1ch. Audio Input
WDR	DWDR	DWDR	Yes (120db)	Yes (120db)	WDR (100db)	DWDR
WIFI	No	Yes	Yes	Yes	No	No
Power Supply	12V DC	12V DC	12V DC	12V DC	12V DC	12V DC or POE
Other Feathures	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI, ROI Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

40

Click for More information

DS-2CD2955FWD- IS



Asan Tejarat



Price (Rials)	۵۶,۸۰۰,۰۰۰
Camera Type	FishEye
Imaging Sensor	1/3" Prog. CMOS
Resolution	5MP (2560x1920/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2
Lens	1.5mm Fix
Viewing Angle	186° Panoramic
IR Range	Up to 8m
Body Type & Standard	-
SD Card Support	Yes (up to 128GB)
Microphone Support	No
WDR	Yes (120db)
WIFI	No
Power Supply	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

برای کنترل موجودی در لیست با
شماره های زیر تماس بگیرید:

021-88769732

021-88171031

021-88512942

	41	42	43	44	45	46
Click for More information	DS-2CD2020F-I	DS-2CD2022WD-I	DS-2CD2042WD-I	DS-2CD2052-I	DS-2CD2T22WD-I5	DS-2CD2T42WD-I3



Price (Rials)	۱۲,۶۳۰,۰۰۰	Call:88512912	Call:88512912	۲۲,۷۰۰,۰۰۰	Call:88512912	۱۸,۴۳۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP (2688x1520/20fps)	5MP (2560x1920/20fps)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	4mm Fix	4mm Fix	4mm Fix	4mm Fix	4mm Fix	4mm Fix
Viewing Angle	79°	79°	79°	79°	79°	79°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m (EXIR)	Up to 50m (EXIR)
Body Type & Standard	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66
SD Card Support	No	No	No	No	No	No
Microphone Support	No	No	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	DWDR	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion

47

48

49

50

51

52

Click for More
information

DS-2CD2T42WD-I5

DS-2CD2T42WD-I8

DS-2CD2T52-I5

DS-2CD2T43G0-I5

DS-2CD2T63G0-I5

DS-2CD2T63G0-I8



Asan Tejarat



	Call:88512912	۲۲,۷۰۰,۰۰۰	۲۴,۹۲۰,۰۰۰	۱۸,۹۴۰,۰۰۰	۲۲,۱۹۰,۰۰۰	۲۳,۵۵۰,۰۰۰
Price (Rials)						
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.9" Prog. CMOS	1/2.9" Prog. CMOS
Resolution	4MP(2688×1520/20fps)	4MP(2688×1520/20fps)	5MP(2560×1920/20fps)	4MP (2688×1520/20fps)	6MP (2688×1520/20fps)	6MP (2688×1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.018Lux @ F2	0.018Lux @ F2	0.018Lux @ F2
Lens	4mm Fix	4mm Fix	4mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix
Viewing Angle	79°	79°	79°	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°/39°
IR Range	Up to 50m (EXIR)	Up to 80m (EXIR)	Up to 50m (EXIR)	Up to 50m	Up to 50m	Up to 80m
Body Type & Standard	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP67	Metal / IP67
SD Card Support	No	No	No	Yes	Yes	Yes
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	DWDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion

53

54

55

56

57

58

Click for More information

DS-2CD2T83G0-I5

DS-2CD2T83G0-I8

DS-2CD2043G0-I

DS-2CD2063G0-I

DS-2CD2083G0-I

DS-2CD1043G0-I



Price (Rials)	۲۶,۶۲۰,۰۰۰	۲۷,۹۹۰,۰۰۰	۱۶,۲۱۰,۰۰۰	۱۹,۴۶۰,۰۰۰	۲۲,۸۷۰,۰۰۰	۱۳,۳۱۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/2.5" Prog. CMOS	1/2.5" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.5" Prog. CMOS	1/3" Prog. CMOS
Resolution	8MP (3840×2160/15fps)	8MP (3840×2160/15fps)	4MP(2688×1520/20fps)	6MP(2688×1520/20fps)	8MP(2688×1520/20fps)	4MP (2688×1520/20fps)
Network Standard	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI
Min. Illustration	0.028Lux @ F2	0.028Lux @ F2	0.018Lux @ F2	0.028Lux @ F2	0.028Lux @ F2	0.028Lux @ F2
Lens	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6mm Fix
Viewing Angle	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°
IR Range	Up to 50m	Up to 80m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	Yes	Yes	Yes	Yes	Yes	No
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC

59

60

61

62

63

64

Click for More information

DS-2CD1643G0-I

DS-2CD2620F-I

DS-2CD2620F-IZ

DS-2CD2622FWD-IS

DS-2CD2642FWD-IS

DS-2CD2642FWD-IZS



Asan Tejarat



Price (Rials)	۲۳,۸۹۰,۰۰۰	۲۱,۸۴۰,۰۰۰	Call:88512912	Call:88512912	Call:88512912	۴۲,۶۶۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	4MP (2688×1520/20fps)	2MP (1920×1080/25FPS)	2MP (1920×1080/25FPS)	2MP (1920×1080/25FPS)	4MP (2688×1520/20fps)	4MP (2688×1520/20fps)
Network Standard	ONVIF, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.018Lux @ F2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP67	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66
SD Card Support	Yes	No	No	No	No	No
Microphone Support	No	No	No	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input
WDR	Yes (120db)	DWDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Motion detection, Tamper Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion

65

66

Click for More information

DS-2CD2652F-IS

DS-2CD2652F-IZS



Asan Tejarat



Price (Rials)	Call:88512912	Call:88512912
Camera Type	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	5MP (2560×1920/20fps)	5MP (2560×1920/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8-12mm Varifocal	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes
Microphone Support	1ch. Audio Input	1ch. Audio Input
WDR	DWDR	DWDR
WIFI	No	No
Power Supply	12V DC or POE	12V DC or POE
Other Feathures	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion

برای کنترل موجودی در لیست با
شماره های زیر تماس بگیرید:

021-88769732

021-88171031

021-88512942

67

68

69

70

71

72

Click for More information

DS-2DE2202I-DE3

DS-2DE3304W-DE

DS-2DE4220IW-DE

DS-2DE5220IW-AE

DS-2DE5230W-AE

DS-2DE4A220IW-DE



Price (Rials)	Call:88512912	Call:88512912	۶۷,۵۱۰,۰۰۰	۱۱۲,۲۶۰,۰۰۰	۱۱۶,۹۷۰,۰۰۰	Call:88512912
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	PTZ
Imaging Sensor	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	3MP(2048x1536/20FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	API, Onvif, ISAPI, CG
Min. Illustration	0.05Lux/F2	0.05Lux/F2	0.05Lux/F1.6	0.02Lux/F1/5	0.01Lux/F1.6	0.01Lux/F1.6
Lens	2.8-6mm Motorized	2.8-12mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized
Optical Zoom	2x	4x	20x	20x	30x	20x
IR Range	-	-	100m	150m	150m	50m
Body Type	Metal	Metal	Metal	Metal	Metal	-
IP Standard	Indoor	IP66	IP66	IP66	IP66	IP66
WDR	No	No	No	No	No	WDR
WIFI	No	No	No	No	No	No
Power Supply	24v AC	24v AC	12VDC & POE(802.3at)	24v AC	12VDC & POE(802.3at)	12VDC & POE(802.3at)
Other Features	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, 3D DNR, HLC, ICR, BLC

73

74

75

76

77

78

Click for More information

DS-2DE7230IW-AE

DS-2DE7220IW-AE

DS-2DE7320IW-AE

DS-2DE7330IW-AE

DS-2DE7420IW-AE

DS-2DE7430IW-AE



Price (Rials)	۱۳۶,۲۰۰,۰۰۰	۱۱۷,۷۵۰,۰۰۰	۱۳۴,۲۴۰,۰۰۰	۱۵۹,۷۵۰,۰۰۰	۱۶۳,۲۸۰,۰۰۰	۱۸۶,۸۳۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP (1920x1080/30FPS)	2MP (2048x1536/20FPS)	2MP (2048x1536/20FPS)	3MP (2048x1536/20FPS)	2MP (2048x1536/20FPS)	3MP (2048x1536/20FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6
Lens	4.3-94mm Motorized	4.3-94mm Motorized	4.7-94mm Motorized	4.3-129mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized
Optical Zoom	30x	20x	20x	20x	20x	20x
IR Range	150m	150m	150m	150m	150m	150m
Body Type	Metal	Metal	Metal	Metal	Metal	PLASTIC
IP Standard	IP66	IP66	IP66	IP66	IP66	IP66
WDR	No	No	No	No	No	No
WIFI	No	No	No	No	No	No
Power Supply	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)
Other Features	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC

79

80

Click for More information

DS-2DE7530IW-AE DS-2PT3326IZ-DE3



Price (Rials)	۲۰۳,۳۲۰,۰۰۰	۷۰,۰۰۰,۰۰۰
Camera Type	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	3MP (2048x1536/20FPS)	2MP (1920x1080/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	API, Onvif, ISAPI, CG
Min. Illustration	0.05Lux/F1.6	0.01Lux/F1.6
Lens	4.3-129mm Motorized	2.8-12mm
Optical Zoom	20x	4x
IR Range	150m	10m
Body Type	Metal	Aluminum alloy
IP Standard	IP66	-
WDR	No	DWDR
WIFI	No	No
Power Supply	12VDC & POE(802.3at)	12VDC & POE(802.3at)
Other Features	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	8x Digital Zoom, ICR

برای کنترل موجودی در لیست با
شماره های زیر تماس بگیرید:

021-88769732

021-88171031

021-88512942

	81	82	83	84	85	86
Click for More information	DS-7104NI-E1/M	DS-7604NI-E1	DS-7604NI-E1/4P	DS-7604NI-K1	DS-7604NI-K1/4P	DS-7604NI-Q1



Price (Rials)	۱۰,۵۸۰,۰۰۰	Call:88512912	۱۸,۴۰۰,۰۰۰	۱۴,۸۶۰,۰۰۰	۲۰,۱۷۰,۰۰۰	۱۴,۸۶۰,۰۰۰
NVR Type	4 Ch NVR	4 Ch NVR	4 Ch POE NVR	4 Ch NVR	4 Ch POE NVR	4 Ch NVR
Input BandWidth	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Audio Input/Output	4Ch. In/ 1Ch. Out	4Ch. In/ 1Ch. Out	4Ch. In/ 1Ch. Out	4Ch. In/ 1Ch. Out	4Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	4Ch. : 1080P	4Ch. : 1080P	4Ch. : 1080P	4Ch. : 1080P 1Ch. : 4K	4Ch. : 1080P 1Ch. : 4K	4Ch. : 1080P
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	-	-	4 POE Ports	-	4 POE Ports	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Feathures	H.264 COMPR	H.264 COMPR	H.264 COMPR	H.265 COMPR Alarm I/O 4/1	H.265 COMPR Alarm I/O 4/1	H.265+ COMPR

87

Click for More
information

DS-7604NI-Q1/4P



Asan Tejarat



Price (Rials)	۲۰,۱۷۰,۰۰۰
NVR Type	4 Ch POE NVR
Input BandWidth	40Mbps
Output Bandwidth	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out
Decoding Capacity	4Ch. : 1080P 1Ch. : 4K
Video Output	1 Port HDMI : 4K 1 Port VGA : 1920P
POE Ports	4 POE Ports
SATA Interface	1 HDD up to 6TB
Network Interface	1 RJ45 100M
Chassis	Standalone 1U
Other Feathures	

	88	89	90	91	92	93
Click for More information	DS-7108NI-E1	DS-7608NI-E2	DS-7608NI-E2/8P	DS-7608NI-K2	DS-7608NI-K2/8P	DS-7608NI-Q1



Price (Rials)	Call:88512912	۱۷,۳۴۰,۰۰۰	۲۹,۰۱۰,۰۰۰	۲۱,۲۳۰,۰۰۰	۳۳,۶۱۰,۰۰۰	۲۰,۰۰۰,۰۰۰
NVR Type	8 Ch POE NVR	8 Ch NVR	8 Ch POE NVR	8 Ch NVR	8 Ch POE NVR	8 Ch NVR
Input BandWidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	160Mbps	80Mbps	80Mbps
Audio Input/Output	8Ch. In/ 1Ch. Out	8Ch. In/ 1Ch. Out	8Ch. In/ 1Ch. Out	8Ch. In/ 1Ch. Out	8Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P	8Ch. : 1080P 2Ch. : 4K	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4k 1 Port VGA : 1920p
POE Ports	-	-	8 POE Ports	-	8 POE Ports	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Feathures	H.264 COMPR	H.264 COMPR	H.264 COMPR	H.265 COMPR Alarm I/O 4/1	H.264 COMPR	H.265+ COMPR

94

Click for More
information

DS-7608NI-Q1/8P



Asan Tejarat



Price (Rials)	۳۲,۰۰۰,۰۰۰
NVR Type	8 Ch POE NVR
Input BandWidth	80Mbps
Output Bandwidth	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out
Decoding Capacity	6Ch. : 720P 4Ch. : 1080P
Video Output	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	8 POE Ports
SATA Interface	1 HDD up to 6TB
Network Interface	1 RJ45 1000M
Chassis	Standalone 1U
Other Feathures	H.265+ COMPR

	95	96	97	98	99	100
Click for More information	DS-7616NI-E2	DS-7616NI-E2/8P	DS-7616NI-E2/16P	DS-7716NI-E4	DS-7716NI-E4/16P	DS-7616NI-K2



Price (Rials)	۱۹,۱۱۰,۰۰۰	۳۰,۴۳۰,۰۰۰	۳۹,۱۳۰,۰۰۰	۳۷,۵۰۰,۰۰۰	Call:88512912	۲۳,۰۰۰,۰۰۰
NVR Type	16 Ch NVR	16 Ch POE NVR	16 Ch POE NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	160Mbps
Audio Input/Output	16Ch. In/ 1Ch. Out 16Ch. : 4CIF	16Ch. In/ 1Ch. Out 16Ch. : 4CIF	16Ch. In/ 1Ch. Out 16Ch. : 4CIF	16Ch. In/ 1Ch. Out 16Ch. : 4CIF	16Ch. In/ 1Ch. Out 16Ch. : 4CIF	16Ch. In/ 1Ch. Out 16Ch. : 4CIF
Decoding Capacity	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	8Ch. : 1080P 2Ch. : 4K
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	8 POE Ports	16 POE Ports	-	16 POE Ports	-
SATA Interface	2 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	2 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	19" 1.5 Case	19" 1.5 Case	Standalone 1U
Other Feathures	H.264 COMPR	H.264 COMPR	H.264 COMPR	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 4/1

101

102

103

104

Click for More information

DS-7616NI-K2/16P

DS-7716NI-K4

DS-7716NI-K4/16P

DS-7616NI-Q2/16P



Price (Rials)	۴۴,۲۲۰,۰۰۰	۴۶,۳۵۰,۰۰۰	Call:88512912	۴۴,۲۲۰,۰۰۰
NVR Type	16 Ch NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	160Mbps	160Mbps	160Mbps	80Mbps
Audio Input/Output	16Ch. In/ 1Ch. Out	16Ch. In/ 1Ch. Out	16Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K	16Ch. : 4CIF 12Ch. : 720P 6Ch. : 1080P
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	16 POE Ports	-	16 POE Ports	16 POE Ports
SATA Interface	2 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	2 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	19" 1.5 Case	19" 1.5 Case	1U chassis
Other Feathures	H.265 COMPR Alarm I/O 4/1	H.265 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4	H.265+ COMPR

105

106

107

108

Click for More information

DS-7732NI-E4

DS-7732NI-E4/16P

DS-7732NI-K4

DS-7732NI-K4/16P



Asan Tejarat



Price (Rials)	۴۹,۱۸۰,۰۰۰	۶۹,۳۴۰,۰۰۰	۵۸,۳۷۰,۰۰۰	۷۷,۱۲۰,۰۰۰
NVR Type	32 Ch NVR	32 Ch NVR	32 Ch NVR	32 Ch POE NVR
Input BandWidth	200Mbps	200Mbps	256Mbps	256Mbps
Output Bandwidth	80Mbps	80Mbps	160Mbps	160Mbps
Audio Input/Output	32Ch. In/ 1Ch. Out 16Ch. : 4CIF	32Ch. In/ 1Ch. Out 16Ch. : 4CIF	32Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	16 POE Ports	-	16 POE Ports
SATA Interface	4 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB
Network Interface	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case
Other Feathures	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4

