

HIKVISION

لیست قیمت رسمی دی ماه ۱۳۹۷

درباره هایک ویژن

شرکت هایک ویژن (Hikvision) یک شرکت چینی فعال در زمینه تولید تجهیزات مداربسته است. این شرکت کار خود را در سال 2001 در شهر هانگ ژو آغاز کرد و مسیر پیشرفت را با سرعتی بالا طی کرد به طوری که در سال 2014 به عنوان سومین تولید کننده بزرگ تجهیزات حفاظتی - امنیتی و اولین تولید کننده تجهیزات مداربسته در جهان شناخته شد.

شرکت هایک ویژن در سال 2013 بیش از 13000 نفر را به صورت مستقیم به اشتغال در آورده که با داشتن تیم تحقیق و توسعه ای 4000 نفری دارای بزرگترین تیم تحقیق و توسعه جهان محسوب می شود. این شرکت دارای 30 نماینده محلی در چین و بیش از 16 نماینده بین المللی در جهان است که تجهیزات این شرکت را به طور فعال توزیع می کنند.

افتخارات هایک ویژن

سومین تولید کننده بزرگ تجهیزات حفاظتی جهان در سال 2014 و 2015
اولین تولید کننده دوربین مداربسته و تجهیزات نظارت تصویری در سال 2015
تولید بیشتر از 20% از کل دستگاه های DVR دنیا
برنده جایزه ملی ZUBR روسیه در سال ۲۰۱۳
برنده جایزه طراحی محصول RED DOT در سال ۲۰۱۲
برنده جایزه طراحی بهترین دوربین IP در Secutech در سال ۲۰۱۲
برنده جایزه "Golden Excellence Award" در سال ۲۰۱۱
برنده جایزه FSdays در سال ۲۰۱۰

تارتن دژ آریانا

نمایندگی بخش محصولات هایک ویژن



"021-88532406, 09901368002"

برای کنترل موجودی در لیست قیمت با شماره های زیر تماس بگیرید:

021-88532406

021-88179342

021-88522641

021-86044903

	1	2	3	4	5	6
Click for More information	DS-2CD2120F-I	DS-2CD2120F-IS	DS-2CD2122FWD-IS	DS-2CD2142FWD-I	DS-2CD2142FWD-IS	DS-2CD2152F-IS
						
Price (Rials)	۱۲,۶۶۰,۰۰۰	Call:88532406	Call:88532406	Call:88532406	۱۷,۶۲۰,۰۰۰	۱۹,۳۱۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	2MP(2560x1920/20fps)	4MP(2560x1920/20fps)	4MP(2688x1520/20fps)	5MP(2560x1920/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8/4/6mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix
Viewing Angle	98.5°/79°	98.5°/79°	98.5°/79°/51	98.5°/79°	98.5°/79°	98.5°/79°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal & plastic / IP67 & IK10	Metal / IP67 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	No	1ch. Audio Input	No	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input
WDR	DWDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

7

8

9

10

11

12

Click for More
information

DS-2CD1123G0-I

DS-2CD1143G0-I

DS-2CD2123G0-IS

DS-2CD2143G0-IS

DS-2CD2163G0-IS

DS-2CD2183G0-IS



Price (Rials)

۱۰,۴۴۰,۰۰۰

۱۴,۰۳۰,۰۰۰

۱۶,۴۲۰,۰۰۰

۱۷,۷۹۰,۰۰۰

۲۱,۲۱۰,۰۰۰

۲۴,۹۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

6MP(2688x1520/20fps)

1/2.5" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

4MP(2688x1520/20fps)

2MP(1920x1080/25FPS)

4MP(2688x1520/20fps)

1/29" Prog. CMOS

8MP(2688x1520/20fps)

Network Standard

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

Min. Illustration

0.01Lux @ F2

0.028Lux @ F2

0.01 Lux @ F1.2

0.018Lux @ F2

0.028Lux @ F2

0.028Lux @ F2

Lens

2.8/4/6mm Fix

2.8/4/6mm Fix

2.8/4/6/8mm Fix

2.8/4/6/8mm Fix

1/29" Prog. CMOS

2.8/4/6/8mm Fix

Viewing Angle

98.5°/79°/51°

98.5°/79°/51°

98.5°/79°/51°/39°

98.5°/79°/51°/39°

98.5°/79°/51°/39°

98.5°/79°/51°/39°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67 & IK10

Metal / IP67 & IK10 No

Metal / IP67 & IK10

Metal / IP67

Metal / IP66 & IK10

Metal / IP67 & IK10

SD Card Support

No

Yes

Yes

Yes

Yes

Yes

Microphone Support

No

1.ch Audio Input

No

No

1.ch Audio Input

1.ch Audio Input

WDR

DWDR

No

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

12V DC or POE

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC

3D DNR, BLC

3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

13

14

15

16

17

18

Click for More
information

DS-2CD2322WD-I

DS-2CD2342WD-I

DS-2CD2352-I

DS-2CD2510F

DS-2CD2520F

DS-2CD2522FWD-I



Price (Rials)

Call:88532406

۱۶,۸۳۰,۰۰۰

۲۵,۱۵۰,۰۰۰

Call:88532406

Call:88532406

Call:88532406

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

4MP(2688x1520/20fps)**5MP(2560x1920/20fps)****1.3MP(1920x1080/25FPS)**

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

Min. Illustration

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

Viewing Angle

98.5°/79°

98.5°/79°

98.5°/79°

98.5°/79°

98.5°/79°

98.5°/79°

IR Range

Up to 30m (EXIR)**Up to 30m (EXIR)****Up to 30m (EXIR)**

Up to 10m

Up to 10m

Up to 10m

Body Type & Standard

Plastic / IP66

Plastic / IP66

Plastic / IP66

Metal / IP66 & IK10**Metal / IP66 & IK10****Metal / IP66 & IK10**

SD Card Support

No

No

No

Yes**Yes****Yes**

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)**Yes (120db)**

DWDR

DWDR

DWDR

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection








3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

	19	20	21	22	23	24
Click for More information	DS-2CD2523G0-IS	DS-2CD2542FWD-IS	DS-2CD2563G0-IS	DS-2CD2720F-I	DS-2CD2720F-IS	DS-2CD2720F-IZ
						
Price (Rials)	۲۰,۷۰۰,۰۰۰	۲۳,۶۹۰,۰۰۰	۲۶,۶۸۰,۰۰۰	۱۸,۹۷۰,۰۰۰	Call:88532406	۲۸,۳۹۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	4MP(2560x1920/20fps)	6MP(2688x1520/20fps)	2MP(1920x1080/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F1.2	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8/4/6mm Fix	2.8mm/4mm Fix	2.8/4/6mm Fix	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8-12mm Motorized
Viewing Angle	98.5°/79°/51	98.5°/79°	98.5°/79°/51	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 10m	Up to 10m	Up to 10m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66	Metal / IP66 & IK10	Metal & Plastic / IP66	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	1.ch Audio Input	1.ch Audio Input	No	No	1.ch Audio Input	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	DWDR	DWDR	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

25

26

27

28

29

30

[Click for More information](#)

DS-2CD2720F-IZS

DS-2CD2722FWD-IS

DS-2CD2723G0-IZS

DS-2CD2732F-IS

DS-2CD2742FWD-IS

DS-2CD2742FWD-IZS



Price (Rials)

Call:88532406

Call:88532406

۳۲,۵۰۰,۰۰۰

Call:88532406

Call:88532406

Call:88532406

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP (1920x1080/25FPS)

2MP (1920x1080/25FPS)

2MP (1920x1080/25FPS)

3MP(2048x1536/20FPS)**4MP(2688x1520/20fps)****4MP(2688x1520/20fps)**

Network Standard

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

2.8-12mm Motorized**2.8-12mm Varifocal****2.8-12mm Motorized****2.8-12mm Varifocal****2.8-12mm Varifocal****2.8-12mm Motorized**

Viewing Angle

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP66 & IK10**Metal / IP66 & IK10****Metal / IP67 & IK10****Metal / IP66 & IK10****Metal / IP66 & IK10****Metal / IP66 & IK10**

SD Card Support

Yes

Yes

Yes

Yes

Yes

Yes

Microphone Support

1ch. Audio Input**1ch. Audio Input**

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input**1ch. Audio Input**

WDR

DWDR

Yes (120db)**Yes (120db)**

DWDR

Yes (120db)**Yes (120db)**

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

	31	32	33	34	35	36
Click for More information	DS-2CD2752F-IS	DS-2CD2752F-IZS	DS-2CD1723G0-I	DS-2CD1743G0-I	DS-2CD2743G0-IZS	DS-2CD2763G0-IZS



Price (Rials)	۴۰,۹۵۰,۰۰۰	Call:88532406	۱۹,۸۴۰,۰۰۰	۲۱,۵۵۰,۰۰۰	۳۵,۹۲۰,۰۰۰	۴۱,۳۹۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	5MP(2560×1920/20fp)	5MP(2560×1920/20fps)	2MP(2688×1520/20fps)	4MP (1920x1080/25FPS)	4MP (2688×1520/20fps)	6MP(2688×1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.018Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Varifocal	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP67 & IK10	Metal / IP67	Metal/ IP67 & IK10	Metal/ IP67 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	1ch. Audio Input	1ch. Audio Input	No	No	No	1ch. Audio Input
WDR	DWDR	DWDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, Motion detection, Tamper Detection, illegal login	3D DNR, BLC, ROI, Motion detection, Tamper Detection	3D DNR, BLC, Motion detection, Tamper Detection, illegal login	3D DNR, BLC, Motion detection, Tamper Detection, illegal login

Click for More
information

DS-2CD2783G0-IZS



Price (Rials)	۴۷,۸۹۰,۰۰۰
Camera Type	Dome
Imaging Sensor	1/3" Prog. CMOS
Resolution	8MP(2688×1520/20fps)
Network Standard	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2
Lens	2.8-12mm Varifocal
Viewing Angle	91.2°~28.3°
IR Range	Up to 30m
Body Type & Standard	Metal/ IP67 & IK10
SD Card Support	Yes
Microphone Support	1ch. Audio Input
WDR	Yes (120db)
WIFI	No
Power Supply	12V DC or POE
Other Features	3D DNR, BLC, Motion detection, Tamper Detection, illegal login

برای کنترل موجودی در لیست قیمت با شماره های زیر تماس بگیرید:

021-88532406

021-88179342

021-88522641

021-86044903

	38	39	40	41	42	43
Click for More information	DS-2CD2E20F-W	DS-2CD2Q10FD-IW	DS-2CV2Q21FD-IW/32GT	DS-2CV2U21FD-IW/32GT	DS-2CD2F22WD-IS	DS-2CD2F42WD-IS
						
Price (Rials)	۱۸,۶۵۰,۰۰۰	۱۶,۷۲۰,۰۰۰	۱۴,۵۱۰,۰۰۰	۱۱,۶۱۰,۰۰۰	Call:88532406	Call:88532406
Camera Type	Roof mount Dome	Indoor Pan-tilt	Indoor Pan-tilt		Pan-Tilt Dome	Pan-Tilt Dome
Imaging Sensor	1/3" Prog. CMOS	1/4" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	1MP (1280x720/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP(2688x1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8mm / 4mm Fix	2.8mm / 4mm Fix	2.8mm Fix	2.8mm Fix	4mm Fix	4mm Fix
Viewing Angle	98.5° / 79°	98.5° / 79°	98.5°	98.5°	79°	79°
IR Range	-	Up to 10m	Up to 10m	Up to 10m	Up to 10m	Up to 10m
Body Type & Standard	Metal / IP66 & IK10	Plastic	Plastic	Plastic	Metal	Metal
SD Card Support	No	Yes (up to 64GB)	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 64GB)	Yes (up to 64GB)
Microphone Support	No	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	1ch. Audio Input	1ch. Audio Input
WDR	DWDR	DWDR	Yes (120db)	NO	Yes (120db)	Yes (120db)
WIFI	Yes	Yes	Yes	Yes	No	No
Power Supply	12V DC	12V DC or POE	12V DC or POE	12V DC	12V DC	12V DC
Other Features	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI, Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	PIR, 3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI Detection	Motorized Pan-Tilt Rotation ,PIR, 3D DNR, BLC, ROI Detection

44

45

46

47

48

49

Click for More
information

DS-2CD2F52F-IS

DS-2CD2420F-IW

DS-2CD2422FWD-IW

DS-2CD2423G0-IW

DS-2CD2442FWD-IW

DS-2CD2D14WD



Price (Rials)

۱۸,۷۵۰,۰۰۰

۱۲,۶۶۰,۰۰۰

Call:88532406

۱۳,۶۹۰,۰۰۰

۱۷,۴۵۰,۰۰۰

۱۳,۰۹۰,۰۰۰

Camera Type

Pan-Tilt Dome

Cube

Cube

Cube

Cube

Miniature

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/4" Prog. CMOS

Resolution

5Mp(2560×1920/20fps)

2MP(1920x1080/25FPS)

2MP (1920x1080/25FPS)

2MP (1920x1080/25FPS)

4MP(2688×1520/20fps)

1MP (1280x720/25FPS)

Network Standard

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F2.0

Lens

4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

2.8mm/4mm Fix

3.6mm Fix

Viewing Angle

79°

98.5°/79°

98.5°/79°

98.5°/79°

98.5°/79°

65°

IR Range

Up to 10m

Up to 10m

Up to 10m

Up to 10m

Up to 10m

-

Body Type & Standard

Metal

Plastic

Plastic

Plastic

Plastic

Metal

SD Card Support

-

Yes (up to 64GB)

Yes (up to 64GB)

Yes (up to 64GB)

Yes (up to 64GB)

No

Microphone Support

1ch. Audio Input

Yes (Build-in Mic & Spkr)

Yes (Build-in Mic & Spkr)

Yes (Build-in Mic & Spkr)

Yes (Build-in Mic & Spkr)

No

WDR

DWDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

WDR (100db)

WIFI

No

Yes

Yes

Yes

Yes

No

Power Supply

12V DC

12V DC

12V DC

12V DC

12V DC

12V DC

Other Features

**Motorized Pan-Tilt
Rotation**, PIR, 3D DNR, BLC,
ROI, Line Crossing
Detection, Intrusion
Detection

PIR, 3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

PIR, 3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

PIR, 3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

PIR, 3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

3D DNR, BLC, ROI, Line
crossing detection,
Intrusion Detection

50

51

Click for More
information

DS-2CD2942F-IS

DS-2CD2955FWD-IS



Price (Rials)	۴۶,۲۴۰,۰۰۰	۵۴,۷۸۰,۰۰۰
Camera Type	FishEye	FishEye
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	4MP(2464x1520/12FPS)	5MP(2560x1920/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	1.6mm Fix	1.5mm Fix
Viewing Angle	186° Panoramic	186° Panoramic
IR Range	Up to 10m	Up to 8m
Body Type & Standard	Plastic	-
SD Card Support	Yes (up to 64GB)	Yes (up to 128GB)
Microphone Support	1ch. Audio Input	No
WDR	DWDR	Yes (120db)
WIFI	No	No
Power Supply	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection

برای کنترل موجودی در لیست قیمت با شماره های زیر تماس بگیرید:

021-88532406

021-88179342

021-88522641

021-86044903

52

53

54

55

56

57

Click for More
information

DS-2CD2020F-I

DS-2CD2022WD-I

DS-2CD2042WD-I

DS-2CD2052-I

DS-2CD2T22WD-I5

DS-2CD2T42WD-I3



Price (Rials)

۱۲,۶۶۰,۰۰۰

Call:88532406

۱۶,۰۰۰,۰۰۰

۱۸,۳۵۰,۰۰۰

Call:88532406

۱۸,۴۳۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2688x1520/20fps)

5MP(2560x1920/20fps)

2MP (1920x1080/25FPS)

4MP(1920x1080/25FPS)

Network Standard

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, PSIA, CGI, ISAPI

Min. Illustration

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

4mm Fix

4mm Fix

4mm Fix

4mm Fix

4mm Fix

4mm Fix

Viewing Angle

79°

79°

79°

79°

79°

79°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m (EXIR)

Up to 30m (EXIR)

Body Type & Standard

Metal / IP66

Metal / IP66

Metal / IP66

Metal / IP66

Metal / IP66

Metal / IP66

SD Card Support

Yes

No

No

No

No

No

Microphone Support

No

No

No

No

No

No

WDR

DWDR

Yes (120db)

Yes (120db)

DWDR

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion

58

59

60

61

62

63

Click for More information

DS-2CD2T42WD-I5

DS-2CD2T42WD-I8

DS-2CD2T52-I5

DS-2CD2T43G0-I5

DS-2CD2T63G0-I5

DS-2CD2T63G0-I8



Price (Rials)	۲۱,۵۵۰,۰۰۰	۲۲,۷۰۰,۰۰۰	۲۴,۹۷۰,۰۰۰	۱۸,۴۸۰,۰۰۰	۲۲,۲۴۰,۰۰۰	۲۳,۶۱۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.9" Prog. CMOS	1/2.9" Prog. CMOS
Resolution	4MP(2688×1520/20fps)	4MP(2688×1520/20fps)	5MP(2560×1920/20fps)	4MP(2688×1520/20fps)	6MP(2688×1520/20fps)	6MP(2688×1520/20fps)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.018Lux @ F2	0.018Lux @ F2	0.018Lux @ F2
Lens	4mm Fix	4mm Fix	4mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix	2.8/4/6/8mm Fix
Viewing Angle	79°	79°	79°	98.5°/79°/51°/39°	98.5°/79°/51°/39°	98.5°/79°/51°/39°
IR Range	Up to 50m (EXIR)	Up to 80m (EXIR)	Up to 50m (EXIR)	Up to 50m	Up to 50m	Up to 80m
Body Type & Standard	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP67	Metal / IP67
SD Card Support	No	No	No	Yes	Yes	Yes
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	DWDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion	3D DNR, BLC, ROI, Line crossing detection, Intrusion

64

65

66

67

68

69

[Click for More information](#)

DS-2CD2T83G0-I5

DS-2CD2T83G0-I8

DS-2CD1043G0-I

DS-2CD2043G0-I

DS-2CD2063G0-I

DS-2CD2083G0-I



Price (Rials)

۲۶,۶۸۰,۰۰۰

۲۸,۰۵۰,۰۰۰

۱۳,۳۴۰,۰۰۰

۱۶,۲۵۰,۰۰۰

۱۹,۵۰۰,۰۰۰

۲۲,۹۲۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.5" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

8MP(3840×2160/15fps) 8MP(3840×2160/15fps) 4MP(2688×1520/20fps) 4MP(2688×1520/20fps) 6MP(2688×1520/20fps) 8MP(2688×1520/20fps)

Network Standard

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

Min. Illustration

0.028Lux @ F2

0.028Lux @ F2

0.028Lux @ F2

0.018Lux @ F2

0.028Lux @ F2

0.028Lux @ F2

Lens

2.8/4/6/8mm Fix

2.8/4/6/8mm Fix

2.8/4/6mm Fix

2.8/4/6/8mm Fix

2.8/4/6/8mm Fix

2.8/4/6/8mm Fix

Viewing Angle

98.5°/79°/51°/39°

98.5°/79°/51°/39°

98.5°/79°/51°

98.5°/79°/51°/39°

98.5°/79°/51°/39°

98.5°/79°/51°/39°

IR Range

Up to 50m

Up to 80m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes

Yes

No

Yes

Yes

Yes

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion

3D DNR, BLC

3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion

70

71

72

73

74

75

Click for More information

DS-2CD1023G0-I

DS-2CD1643G0-I

DS-2CD2620F-I

DS-2CD2683G0-IZS

DS-2CD2643G0-IZS

DS-2CD2663G0-IZS



Price (Rials)

9,750,000

23,950,000

Call:88532406

47,890,000

35,920,000

41,390,000

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

4MP(2688x1520/20fps)

2MP(1920x1080/25FPS)

8MP(2688x1520/20fps)

4MP (2688x1520/20fps)

6MP(2688x1520/20fps)

Network Standard

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, PSIA, CGI, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

ONVIF, ISAPI

Min. Illustration

0.01Lux @ F1.2

0.018Lux @ F2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.018Lux @ F1.6

0.01Lux @ F1.2

Lens

2.8/4/6mm Fix

2.8-12mm Varifocal

2.8-12mm Varifocal

2.8-12mm Varifocal

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

98.5°/79°/51°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 50m

Up to 50m

Up to 50m

Body Type & Standard

Metal/ IP67

Metal / IP67

Metal / IP66

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

No

Yes

No

Yes

Yes

Yes

Microphone Support

No

No

No

No

1ch. Audio Input

No

WDR

DWDR

Yes (120db)

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, Motion detection, Tamper Detection, illegal login

3D DNR, BLC, ROI, Motion detection, Tamper Detection

3D DNR, BLC, ROI, Line crossing detection, Intrusion

3D DNR, BLC, Motion detection, Tamper Detection, illegal login

3D DNR, BLC, Motion detection, Tamper Detection, illegal login

3D DNR, BLC, Motion detection, Tamper Detection, illegal login

76

77

78

79

80

81

Click for More information

DS-2CD2620F-IZ

DS-2CD2622FWD-IS

DS-2CD2642FWD-IS

DS-2CD2642FWD-IZS

DS-2CD2652F-IS

DS-2CD2652F-IZS



Price (Rials)

Call:88532406

Call:88532406

Call:88532406

Call:8853240

Call:88532406

Call:88532406

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS) 2MP (1920x1080/25FPS) 4MP(2688x1520/20fps) 4MP(2688x1520/20fps) 5MP(2560x1920/20fps) 5MP(2560x1920/20fps)

Network Standard

ONVIF, PSIA, CGI, ISAPI ONVIF, PSIA, CGI, ISAPI ONVIF, PSIA, CGI, ISAPI ONVIF, PSIA, CGI, ISAPI ONVIF, PSIA, CGI, ISAPI ONVIF, PSIA, CGI, ISAPI

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

2.8-12mm Motorized 2.8-12mm Varifocal 2.8-12mm Varifocal 2.8-12mm Motorized 2.8-12mm Varifocal 2.8-12mm Motorized

Viewing Angle

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP66

Metal / IP66

Metal / IP66

Metal / IP66

Metal / IP66 & IK10

Metal / IP66 & IK10

SD Card Support

No

No

No

No

Yes

Yes

Microphone Support

No

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input

WDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

DWDR

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion3D DNR, BLC, ROI,
Line crossing
detection, Intrusion

82

83

Click for More
information

DS-2CD1623G0-I

DS-2CD1623G0-IZ



Price (Rials)	۱۹,۸۴۰,۰۰۰	۲۲,۲۴۰,۰۰۰
Camera Type	Bullet	Bullet
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(2560×1920/20fps)	2MP(2560×1920/20fps)
Network Standard	ONVIF, ISAPI	ONVIF, ISAPI
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8-12mm Varifocal	2.8-12mm Motorized
Viewing Angle	91.2°~28.3°Up to	91.2°~28.3°
IR Range	30m	Up to 30m
Body Type & Standard	Metal / IP67	Metal / IP67
SD Card Support	Yes	Yes
Microphone Support	NO	NO
WDR	DWDR	DWDR
WIFI	No	No
Power Supply	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI	3D DNR, BLC, ROI


برای کنترل موجودی در لیست قیمت با شماره های زیر تماس بگیرید:

021-88532406

021-88179342

021-88522641

021-86044903

	84	85	86	87	88	89
Click for More information	DS-2DE2202I-DE3	DS-2DE3304W-DE	DS-2DE4220IW-DE	DS-2DE5220IW-AE	DS-2DE5230W-AE	DS-2DE4A220IW-DE
						
Price (Rials)	۲۰,۰۰۰,۰۰۰	Call:88532406	۵۸,۸۴۰,۰۰۰	۹۷,۸۳۰,۰۰۰	۱۰۱,۹۳۰,۰۰۰	۷۵,۲۶۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	PTZ
Imaging Sensor	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	3MP(2048x1536/20FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)	2MP (1920x1080/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	API, Onvif, ISAPI, CG
Min. Illustration	0.05Lux/F2	0.05Lux/F2	0.05Lux/F1.6	0.02Lux/F1/5	0.01Lux/F1.6	0.01Lux/F1.6
Lens	2.8-6mm Motorized	2.8-12mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized
Optical Zoom	2x	4x	20x	20x	30x	20x
IR Range	-	-	100m	150m	150m	50m
Body Type	Metal	Metal	Metal	Metal	Metal	-
IP Standard	Indoor	IP66	IP66	IP66	IP66	IP66
WDR	No	No	No	No	No	WDR
WIFI	No	No	No	No	No	No
Power Supply	24v AC	24v AC	12VDC & POE (802.3at)	24v AC	12VDC & POE (802.3at)	12VDC & POE (802.3at)
Other Features	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC	16x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, 3D DNR, HLC, ICR, BLC

	90	91	92	93	94	95
Click for More information	DS-2DE7230IW-AE	DS-2DE7220IW-AE	DS-2DE7320IW-AE	DS-2DE7330IW-AE	DS-2DE7420IW-AE	DS-2DE7430IW-AE



Price (Rials)	118,700,000	102,620,000	134,240,000	Call:88532406	142,300,000	156,270,000
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP (1920x1080/30FPS)	2MP (2048x1536/20FPS)	3MP (2048x1536/20FPS)	3MP (2048x1536/20FPS)	4MP (2048x1536/20FPS)	4MP (2048x1536/20FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI	ONVIF, PSIA, CGI, ISAPI
Min. Illustration	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6
Lens	4.3-94mm Motorized	4.3-94mm Motorized	4.7-94mm Motorized	4.3-129mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized
Optical Zoom	30x	20x	20x	20x	20x	30x
IR Range	150m	150m	150m	150m	150m	150m
Body Type	Metal	Metal	Metal	Metal	Metal	Metal
IP Standard	IP66	IP66	IP66	IP66	IP66	IP66
WDR	No	No	No	No	No	No
WIFI	No	No	No	No	No	No
Power Supply	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)	12VDC & POE(802.3at)
Other Features	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC

96

97

Click for More
information

DS-2DE7530IW-AE

DS-2PT3326IZ-DE3



Price (Rials)	۱۷۵,۱۲۰,۰۰۰	۷۷,۹۷۰,۰۰۰
Camera Type	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	5MP (2048x1536/20FPS)	2MP (1920x1080/30FPS)
Network Standard	ONVIF, PSIA, CGI, ISAPI	API, Onvif, ISAPI, CG
Min. Illustration	0.05Lux/F1.6	0.01Lux/F1.6
Lens	4.3-129mm Motorized	2.8-12mm
Optical Zoom	30x	4x
IR Range	150m	10m
Body Type	Metal	Aluminum alloy
IP Standard	IP66	-
WDR	No	DWDR
WIFI	No	No
Power Supply	12VDC & POE(802.3at)	12VDC & POE(802.3at)
Other Features	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	8x Digital Zoom, ICR

برای کنترل موجودی در لیست قیمت با شماره های زیر تماس بگیرید:

021-88532406

021-88179342

021-88522641

021-86044903

	98	99	100	101	102	103
Click for More information	DS-7104NI-E1/M	DS-7604NI-E1	DS-7604NI-E1/4P	DS-7604NI-K1	DS-7604NI-K1/4P	DS-7604NI-Q1



Price (Rials)	۱۰,۵۸۰,۰۰۰	۱۱,۱۳۰,۰۰۰	۱۵,۹۲۰,۰۰۰	۱۲,۵۰۰,۰۰۰	۱۷,۴۵۰,۰۰۰	۱۲,۵۰۰,۰۰۰
NVR Type	4 Ch NVR	4 Ch NVR	4 Ch POE NVR	4 Ch NVR	4 Ch POE NVR	4 Ch NVR
Input BandWidth	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	4Ch. : 1080P	4Ch. : 1080P	4Ch. : 1080P	4Ch. : 1080P 1Ch. : 4K	4Ch. : 1080P 1Ch. : 4K	4Ch. : 1080P
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	-	-	4 POE Ports	-	4 POE Ports	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.264 COMPR	H.264 COMPR	H.264 COMPR	H.265 COMPR Alarm I/O 4/1	H.265 COMPR Alarm I/O 4/1	H.265+ COMPR

104

Click for More
information

DS-7604NI-Q1/4P



Price (Rials)	۱۷,۴۵۰,۰۰۰
NVR Type	4 Ch POE NVR
Input BandWidth	40Mbps
Output Bandwidth	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out
Decoding Capacity	4Ch. : 1080P 1Ch. : 4K
Video Output	1 Port HDMI : 4K 1 Port VGA : 1920P
POE Ports	4 POE Ports
SATA Interface	1 HDD up to 6TB
Netword Interface	1 RJ45 100M
Chassis	Standalone 1U
Other Feathures	

	105	106	107	108	109	110
Click for More information	DS-7108NI-E1	DS-7608NI-E2	DS-7608NI-E2/8P	DS-7608NI-K2	DS-7608NI-K2/8P	DS-7608NI-Q1



Price (Rials)	Call:88532406	۱۵,۵۸۰,۰۰۰	۲۵,۱۰۰,۰۰۰	۱۹,۰۸۰,۰۰۰	۳۰,۲۰۰,۰۰۰	۱۷,۳۱۰,۰۰۰
NVR Type	8 Ch POE NVR	8 Ch NVR	8 Ch POE NVR	8 Ch NVR	8 Ch POE NVR	8 Ch NVR
Input BandWidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	160Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P	8Ch. : 1080P 2Ch. : 4K	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4k 1 Port VGA : 1920p
POE Ports	-	-	8 POE Ports	-	8 POE Ports	-
SATA Interface	1 HDD up to 6TB	1 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Features	H.264 COMPR	H.264 COMPR	H.264 COMPR	H.265 COMPR Alarm I/O 4/1	H.264 COMPR	H.265+ COMPR

111

112

Click for More
information

DS-7608NI-Q1/8P

DS-7608NI-Q2



Price (Rials)	۲۸,۰۸۰,۰۰۰	۱۹,۰۸۰,۰۰۰
NVR Type	8 Ch POE NVR	8 Ch NVR
Input BandWidth	80Mbps	80Mbps
Output Bandwidth	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	6Ch. : 720P 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P
Video Output	1 Port HDMI : 4k 1 Port VGA : 1920P	1 Port HDMI : 4k 1 Port VGA : 1920p
POE Ports	8 POE Ports	-
SATA Interface	1 HDD up to 6TB	2 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U
Other Features	H.265+ COMPR	H.265+ COMPR

	113	114	115	116	117	118
Click for More information	DS-7616NI-E2	DS-7616NI-E2/8P	DS-7616NI-E2/16P	DS-7716NI-E4	DS-7716NI-E4/16P	DS-7616NI-K2



Price (Rials)	۱۷,۱۷۰,۰۰۰	۲۶,۳۲۰,۰۰۰	۳۵,۲۲۰,۰۰۰	۳۷,۴۴۰,۰۰۰	۵۶,۱۹۰,۰۰۰	۲۰,۶۷۰,۰۰۰
NVR Type	16 Ch NVR	16 Ch POE NVR	16 Ch POE NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	16Ch. : 4CIF	16Ch. : 4CIF	16Ch. : 4CIF	16Ch. : 4CIF	16Ch. : 4CIF	8Ch. : 1080P 2Ch. : 4K
	12Ch. : 720P	12Ch. : 720P	12Ch. : 720P	12Ch. : 720P	12Ch. : 720P	
	6Ch. : 1080P	6Ch. : 1080P	6Ch. : 1080P	6Ch. : 1080P	6Ch. : 1080P	
Video Output	1 Port HDMI:1080P	1 Port HDMI:1080P	1 Port HDMI:1080P	1 Port HDMI:1080P	1 Port HDMI:1080P	1 Port HDMI : 4K
	1 Port VGA:1080P	1 Port VGA:1080P	1 Port VGA:1080P	1 Port VGA:1080P	1 Port VGA:1080P	1 Port VGA : 1080P
POE Ports	-	8 POE Ports	16 POE Ports	-	16 POE Ports	-
SATA Interface	2 HDD up to 6TB	2 HDD up to 6TB	2 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	2 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	19" 1.5 Case	19" 1.5 Case	Standalone 1U
Other Features	H.264 COMPR	H.264 COMPR	H.264 COMPR	1 E-SATA Port	1 E-SATA Port	H.265 COMPR Alarm I/O 4/1
				H.264 COMPR Alarm I/O 16/4	H.264 COMPR Alarm I/O 16/4	

	119	120	121	122	123
Click for More information	DS-7616NI-K2/16P	DS-7716NI-K4	DS-7716NI-K4/16P	DS-7616NI-Q1	DS-7616NI-Q2/16P



Price (Rials)	۴۰,۰۰۰,۰۰۰	۴۶,۲۷۰,۰۰۰	۶۳,۲۵۰,۰۰۰	۱۸,۰۰۰,۰۰۰	۴۰,۰۰۰,۰۰۰
NVR Type	16 Ch NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	160Mbps	160Mbps	160Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K	16Ch. : 4CIF 12Ch. : 720P 6Ch. : 1080P	16Ch. : 4CIF 12Ch. : 720P 6Ch. : 1080P
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA : 1920P	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	16 POE Ports	-	16 POE Ports	16 POE Ports	16 POE Ports
SATA Interface	2 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	1 HDD up to 6TB	2 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	19" 1.5 Case	19" 1.5 Case	1U chassis	1U chassis
Other Features	H.265 COMPR Alarm I/O 4/1	H.265 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4	H.265+ COMPR	H.265+ COMPR

	124	125	126	127
Click for More information	DS-7732NI-E4	DS-7732NI-E4/16P	DS-7732NI-K4	DS-7732NI-K4/16P



Price (Rials)	۴۹,۱۰۰,۰۰۰	۶۷,۰۳۰,۰۰۰	۵۸,۲۸,۰۰۰	۷۴,۱۳۰,۰۰۰
NVR Type	32 Ch NVR	32 Ch NVR	32 Ch NVR	32 Ch POE NVR
Input BandWidth	200Mbps	200Mbps	256Mbps	256Mbps
Output Bandwidth	80Mbps	80Mbps	160Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out 16Ch. : 4CIF	1Ch. In/ 1Ch. Out 16Ch. : 4CIF	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	12Ch. : 720P 6Ch. : 1080P	12Ch. : 720P 6Ch. : 1080P	8Ch. : 1080P 2Ch. : 4K	8Ch. : 1080P 2Ch. : 4K
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	16 POE Ports	-	16 POE Ports
SATA Interface	4 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 6TB
Network Interface	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case
Other Features	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	1 E-SATA Port H.264 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4	H.265 COMPR Alarm I/O 16/4