

HIKVISION

لیست قیمت رسمی شهریور ۱۳۹۸

درباره هایک ویژن

شرکت هایک ویژن (Hikvision) یک شرکت چینی فعال در زمینه تولید تجهیزات مدار بسته است. این شرکت کار خود را در سال 2001 در شهر هانگ ژو آغاز کرد و مسیر پیشرفت را با سرعتی بالا طی کرد به طوری که در سال 2014 به عنوان سومین تولید کننده بزرگ تجهیزات حفاظتی امنیتی و اولین تولید کننده تجهیزات مدار بسته در جهان شناخته شد. شرکت هایک ویژن در سال 2013 بیش از 13000 نفر را به صورت مستقیم به اشتغال در آورده که با داشتن تیم تحقیق و توسعه ای 4000 نفری دارای بزرگترین تیم تحقیق و توسعه جهان محسوب می شود. این شرکت دارای 30 نماینده محلی در چین و بیش از 16 نماینده بین المللی در جهان است که تجهیزات این شرکت را به طور فعال توزیع می کنند.

تارتن دژ آریانا

نمایندگی پخش محصولات هایک ویژن



افتخارات هایک ویژن

سومین تولید کننده بزرگ تجهیزات حفاظتی جهان در سال 2014 و 2015
اولین تولید کننده دوربین مدار بسته و تجهیزات نظارت تصویری در سال 2015
تولید بیشتر از 20% از کل دستگاه های DVR دنیا
برنده جایزه ملی ZUBR روسیه در سال ۲۰۱۳
برنده جایزه طراحی محصول RED DOT در سال ۲۰۱۲
برنده جایزه طراحی بهترین دوربین IP در Secutech در سال ۲۰۱۲
برنده جایزه "Golden Excellence Award" در CPSE سال ۲۰۱۱
برنده جایزه FSdays در سال ۲۰۱۰

برای کنترل موجودی در لیست قیمت با شماره زیر تماس بگیرید:

021-88500020

(20 خط)

	1	2	3	4	5	6
Click for More information	DS-2CD2120F-I	DS-2CD2120F-IS	DS-2CD2142FWD-I	DS-2CD2152F-IS	DS-2CD1123G0-I	DS-2CD1143G0-I
						
Price (Rials)	۱۶,۶۹۰,۰۰۰	۱۶,۶۹۰,۰۰۰	Call:88500020	۲۵,۴۶۰,۰۰۰	۱۳,۷۶۰,۰۰۰	۱۸,۴۹۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	4MP(2560x1920/20fps)	5MP(2560x1920/20fps)	2MP(1920x1080/25FPS)	4MP(2560x1440/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.028Lux @ F2
Lens	2.8/4mm Fix	2.8/4mm Fix	2.8/4mm Fix	4/6mm Fix	2.8mm Fix	2.8mm Fix
Viewing Angle	98.5°	98.5°/79	98.5°/79	79/51°	98.5°	98.5°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m (EXIR)
Body Type & Standard	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP67 & IK10	Metal / IP67& IK10	Metal / IP67& IK10	Metal / IP67 & IK10
SD Card Support	Yes	Yes	Yes	Yes	No	Yes
Microphone Support	No	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	No	No
WDR	DWDR	DWDR	Yes (120db)	Yes (120db)	DWDR	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP

7

8

9

10

11

12

Click for More
information

DS-2CD2123G0-IS

DS-2CD2143G0-IS

DS-2CD2163G0-IS

DS-2CD2183G0-IS

DS-2CD2342WD-I

DS-2CD2352-I



Price (Rials)	٢١,٦٥٠,٠٠٠	٢٣,٤٥٠,٠٠٠	٢٧,٩٦٠,٠٠٠	٣٢,٩٢٠,٠٠٠	٢٢,١٩٠,٠٠٠	٣٣,١٥٠,٠٠٠
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.5" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	4MP(2688x1520/20fps)	6MP(3072x2048/20fps)	8MP(3840x2160/15fps)	4MP(2560x1920/20fps)	5MP(2560x1920/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01 Lux @ F2	0.01 Lux @ F2	0.028 Lux @ F2	0.028 Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8mm Fix	2.8mm Fix	2.8mm Fix	2.8mm Fix	2.8/4/6mm Fix	2.8/4/6mm Fix
Viewing Angle	98.5°	98.5°	98.5°	98.5°	98.5°/79°/51	98.5°/79°/51
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m (EXIR)	Up to 30m (EXIR)
Body Type & Standard	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10	Metal / IP67 & IK10	Plastic / IP67	Plastic / IP67
SD Card Support	Yes	Yes	Yes	Yes	No	No
Microphone Support	No	1.ch Audio Input	1.ch Audio Input	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP

13

14

15

16

17

18

[Click for More information](#)

DS-2CD2543G0-IS

DS-2CD2520F

DS-2CD2523G0-IS

DS-2CD2542FWD-IS

DS-2CD2563G0-IS

DS-2CD2720F-I



Price (Rials)	۲۴,۵۰۰,۰۰۰	۱۷,۱۶۰,۰۰۰	۲۷,۲۹۰,۰۰۰	۳۰,۳۵۹,۰۰۰	۳۵,۲۱۷,۰۰۰	۲۵,۰۰۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Mini Dome	Dome
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	2MP(1920x1080/25FPS)	4MP(2688x1520/20fps)	6MP(3072 x 2048/20fps)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8/4/6mm Fix	4 mm Fix	2.8/4/6mm Fix	4 mm Fix	2.8/4/6mm Fix	2.8-12mm Varifocal
Viewing Angle	98.5°/79°/51	79°	98.5°/79°/51	79°	98.5°/79°/51	91.2°~28.3°
IR Range	Up to 10m (EXIR)	-	Up to 10m	Up to 10m	Up to 10m	Up to 30m
Body Type & Standard	Metal / IP66	Metal / IP66	Metal / IP66	Metal / IP66 & IK08	Metal&Plastic / IP66	Metal / IP66 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	No	No	1.ch Audio Input	Built in microphone	No	No
WDR	Yes (120db)	DWDR	Yes (120db)	Yes (120db)	Yes (120db)	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, H.264+ COMP

19

20

21

22

23

24

Click for More
information

DS-2CD2720F-IZ

DS-2CD2723G0-IZS

DS-2CD2742FWD-IZS

DS-2CD2742FWD-IZS

DS-2CD2752F-IZS

DS-2CD1723G0-I



Price (Rials)	۳۷,۴۳۰,۰۰۰	۴۲,۸۵۰,۰۰۰	Call:88500020	Call:88500020	Call:88500020	۲۶,۱۶۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP(2688x1520/20fps)	4MP(2688x1520/20fps)	5MP(2560x1920/20fps)	2MP(2688x1520/20FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.7-12mm Motorized	2.8-12mm Motorized	2.8-12mm Varifocal	2.8-12mm Motorized	2.8-12mm Motorized	2.8-12mm Varifocal
Viewing Angle	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°	91.2°~28.3°
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66 & IK10	Metal / IP67 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal / IP66 & IK10	Metal/ IP67 & IK10
SD Card Support	Yes	Yes	Yes	Yes	Yes	Yes
Microphone Support	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	1ch. Audio Input	No
WDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)	DWDR	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP

25

26

27

28

Click for More
information

DS-2CD1743G0-I

DS-2CD2743G0-IZS

DS-2CD2763G0-IZS

DS-2CD2783G0-IZS



Price (Rials)

۲۸,۴۲۰,۰۰۰

۴۷,۳۶۰,۰۰۰

۵۴,۵۷۰,۰۰۰

۶۳,۱۴۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

4MP (2560x1440/20FPS)

4MP (2688x1520/20fps)

6MP(3072x2048/20fps)

8MP(3840x2160/15fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.018Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

0.01Lux @ F2

Lens

2.8-12mm Varifocal

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 30m (EXIR)

Up to 30m (EXIR)

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal/ IP67 & IK10

Metal/ IP67 & IK10

Metal/ IP67 & IK10

SD Card Support

Yes

Yes

Yes

Yes

Microphone Support

No

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,
H.265+ COMP3D DNR, BLC, ROI, VCA,
H.265+ COMP3D DNR, BLC, ROI, VCA,
H.265+ COMP3D DNR, BLC, ROI, VCA,
H.265+ COMP

برای کنترل موجودی در لیست قیمت با شماره زیر تماس بگیرید:

021-88500020

(20 خط)

29

30

31

32

33

34

[Click for More information](#)

DS-2CD2E20F-W

DS-2CD2Q10FD-IW

DS-2CV2Q21FD-IW

DS-2CV2U21FD-IW

DS-2CD2F52F-IS

DS-2CD2420F-IW



Price (Rials)	۲۴,۵۸۰,۰۰۰	۲۲,۰۵۰,۰۰۰	۱۹,۱۷۰,۰۰۰	۱۵,۳۴۰,۰۰۰	۲۴,۷۱۰,۰۰۰	۱۶,۶۹۰,۰۰۰
Camera Type	Roof mount Dome	Indoor Pan-tilt	Indoor Pan-tilt	CUBE	Pan-Tilt Dome	Cube
Imaging Sensor	1/3" Prog. CMOS	1/4" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	1MP (1280x720/25FPS)	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	5Mp(2560x1920/20fps)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F1.2	0.01Lux @ F2
Lens	4mm Fix	4mm Fix	2.8mm Fix	2.8mm Fix	2.8/4/6mm Fix	2.8mm Fix
Viewing Angle	79°	79°	98.5°	98.5°	98.5°/79°/51	98.5°
IR Range	-	Up to 10m	Up to 5m	Up to 10m	Up to 10m	Up to 10m
Body Type & Standard	-	Plastic	Plastic	Plastic	Metal / IP67	Plastic
SD Card Support	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 128GB)	Yes (up to 64GB)
Microphone Support	No	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	1ch. Audio Input	Yes (Build-in Mic & Spkr)
WDR	DWDR	DWDR	DWDR	DWDR	DWDR	DWDR
WIFI	Built in WIFI	Built in WIFI	Built in WIFI	Built in WIFI	No	Yes
Power Supply	12V DC	12V DC or POE	12V DC or POE	12V DC	12V DC	12V DC
Other Features	3D DNR, BLC, ROI, H.264 COMP	Motorized Pan-Tilt Rotation, PIR, 3DDNR, BLC, ROI, VCA	3D DNR, BLC, ROI, VCA, H.264 COMP	3D DNR, BLC, ROI, VCA, H.264 COMP	Motorized Pan-Tilt Rotation, 3DDNR, BLC, ROI	3D DNR, BLC, ROI, H.264+ COMP, PIR

35

36

37

38

39

40

Click for More
information

DS-2CD2422FWD-IW

DS-2CD2423G0-IW

DS-2CD2442FWD-IW

DS-2CD2D14WD

DS-2CD2942F-IS

DS-2CD2955FWD-IS



Price (Rials)	Call:88500020	Call:88500020	۲۳,۰۰۰,۰۰۰	۱۷,۲۵۰,۰۰۰	۶۱,۰۳۶,۰۰۰	۶۵,۹۲۰,۰۰۰
Camera Type	Cube	Cube	Cube	Miniature	FishEye	FishEye
Imaging Sensor	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS	1/4" Prog. CMOS	1/3" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	2MP (1920x1080/25FPS)	2MP (1920x1080/25FPS)	4MP(2560x1440/20fps)	1MP (1280x720/25FPS)	4MP(2464x1520/12FPS)	5MP(2560x1920/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm Fix	3.6mm Fix	1.6mm Fix	1.05 mm
Viewing Angle	98.5°/79°	98.5°/79°	98.5°	65°	186° Panoramic	186° Panoramic
IR Range	Up to 10m	Up to 10m	Up to 10m	Up to 10m	Up to 10m	Up to 8m
Body Type & Standard	Plastic	Plastic	Plastic	Metal	Plastic	-
SD Card Support	Yes (up to 64GB)	Yes (up to 64GB)	Yes (up to 64GB)	No	Yes (up to 64GB)	Yes (up to 128GB)
Microphone Support	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	Yes (Build-in Mic & Spkr)	No	1ch. Audio Input	1ch. Audio Input
WDR	Yes (120db)	Yes (120db)	Yes (120db)	WDR (100db)	DWDR	Yes (120db)
WIFI	Yes	Yes	Yes	No	No	No
Power Supply	12V DC	12V DC	12V DC	12V DC	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.264+ COMP,PIR	3D DNR, BLC, ROI, VCA, H.264 COMP	3D DNR, BLC, ROI, Line crossing detection, Intrusion Detection	3D DNR, BLC, ROI, VCA, HLC, H.265+ COMP

برای کنترل موجودی در لیست قیمت با شماره زیر تماس بگیرید:

021-88500020

(20 خط)

41

42

43

44

[Click for More information](#)

DS-2CD2020F-I

DS-2CD2042WD-I

DS-2CD2052-I

DS-2CD1323G0-I



Price (Rials)	۱۶,۶۹۰,۰۰۰	۲۳,۲۵۰,۰۰۰	۲۴,۱۹۰,۰۰۰	۱۳,۵۳۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Dome
Imaging Sensor	1/2.8" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/25FPS)	4MP(2688x1520/20fps)	5MP(2560x1920/20fps)	2MP(1920x1080/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	4mm Fix	4mm Fix	4mm Fix	2.8/4/6mm Fix
Viewing Angle	79°	79°	79°	98.5°/79°/51
IR Range	Up to 30m	Up to 30m	Up to 30m	Up to 30m
Body Type & Standard	Metal / IP66	Metal / IP67	Metal / IP66	Metal / IP67
SD Card Support	Yes	No	No	No
Microphone Support	No	No	No	No
WDR	DWDR	Yes (120db)	No	DWDR
WIFI	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, H.265+ COMP

45

46

47

48

49

50

Click for More information

DS-2CD2T52-I5

DS-2CD2T43G0-I5

DS-2CD2T63G0-I5

DS-2CD2T63G0-I8

DS-2CD2T83G0-I5

DS-2CD2T83G0-I8



Price (Rials)	٣٢,٩٢٠,٠٠٠	٢٤,٣٦٠,٠٠٠	٢٩,٣٢٠,٠٠٠	٣١,١٢٠,٠٠٠	٣٥,١٨٠,٠٠٠	٣٦,٩٨٠,٠٠٠
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.9" Prog. CMOS	1/2.9" Prog. CMOS	1/2.5" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	5MP(2560×1920/20fps)	4MP(2688×1520/20fps)	6MP(3072×2048/20fps)	6MP(3072×2048/20fps)	8MP(3840×2160/15fps)	8MP(3840×2160/15fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.028Lux @ F2	0.028Lux @ F2
Lens	4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix	2.8mm/4mm Fix
Viewing Angle	79°	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°	98.5°/79°
IR Range	Up to 50m (EXIR)	Up to 50m (EXIR)	Up to 50m (EXIR)	Up to 80m (EXIR)	Up to 50m (EXIR)	Up to 80m (EXIR)
Body Type & Standard	Metal / IP66	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67	Metal / IP67
SD Card Support	No	Yes	Yes	Yes	Yes	Yes
Microphone Support	No	No	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.264+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR

51

52

53

54

55

56

Click for More
information

DS-2CD1043G0-I

DS-2CD2043G0-I

DS-2CD2063G0-I

DS-2CD2083G0-I

DS-2CD1023G0-I

DS-2CD1643G0-I



Price (Rials)	۱۷,۵۹۰,۰۰۰	۲۱,۴۳۰,۰۰۰	۲۵,۷۱۰,۰۰۰	۳۰,۲۲۰,۰۰۰	۱۲,۸۶۰,۰۰۰	۳۱,۵۷۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Bullet
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.5" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS
Resolution	4MP(2560×1440/20fps)	4MP(2688×1520/20fps)	6MP(3072×2048/20fps)	8MP(3840×2160/20fps)	2MP(1920×1080/25FPS)	4MP(2560×1440/20fps)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.028Lux @ F2	0.01Lux @ F2	0.01Lux @ F2	0.028Lux @ F2	0.01Lux @ F2	0.01Lux @ F2
Lens	2.8mmFix	2.8mm Fix	2.8mm Fix	2.8mm Fix	2.8mm Fix	2.8-12mm Varifocal
Viewing Angle	98.5°	98.5°	98.5°	98.5°	98.5°	91.2°~28.3°
IR Range	Up to 30m (EXIR)	Up to 30m	Up to 30m	Up to 30m	Up to 30m	Up to 30m (EXIR)
Body Type & Standard	Metal / IP66	Metal / IP67	Metal / IP66	Metal / IP66	Metal / IP67	Metal / IP67
SD Card Support	No	Yes	Yes	Yes	No	Yes
Microphone Support	No	No	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	Yes (120db)	DWDR	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR

57

58

59

60

61

62

[Click for More information](#)

DS-2CD2620F-I

DS-2CD2683G0-IZS

DS-2CD2643G0-IZS

DS-2CD2663G0-IZS

DS-2CD1623G0-I

DS-2CD1623G0-IZ



Price (Rials)

۲۸,۸۷۰,۰۰۰

۶۳,۱۴۰,۰۰۰

۴۷,۳۶۰,۰۰۰

۵۴,۵۷۰,۰۰۰

۲۶,۱۶۰,۰۰۰

۲۹,۳۲۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/2.9" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

8MP(3840x2160/15fps)

4MP(2688x1520/25fps)

6MP(3072x2048/20fps)

2MP(2560x1920/20fps)

2MP(2560x1920/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F1.2

0.018Lux @ F1.6

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8-12mm Varifocal

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm varifocal

2.8-12mm Motorized

Viewing Angle

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

91.2°~28.3°

IR Range

Up to 30m

Up to 50m

Up to 50m

Up to 50m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP66

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67

Metal / IP67

SD Card Support

Yes

Yes

Yes

Yes

Yes

Yes

Microphone Support

No

1ch. Audio Input

1ch. Audio Input

1ch. Audio Input

NO

NO

WDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

DWDR

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA, H.264 COMP

3D DNR, BLC, VCA, Face detection, H.265+ COMP

3D DNR, BLC, VCA, H.265+ COMP

3D DNR, BLC, VCA, Face detection, H.265+ COMP

3D DNR, BLC, ROI

3D DNR, BLC, ROI

برای کنترل موجودی در لیست قیمت با شماره زیر تماس بگیرید:

021-88500020

(10 خط)

63

64

65

66

67

68

Click for More
information

DS-2DE2202I-DE3

DS-2DE3304W-DE

DS-2DE4220IW-DE

DS-2DE5220IW-AE

DS-2DE5230W-AE

DS-2DE4A220IW-DE



Price (Rials)

۲۶,۴۰۰,۰۰۰

Call:88500020

۷۷,۵۷۰,۰۰۰

۱۲۸,۹۸۰,۰۰۰

۱۳۴,۳۹۰,۰۰۰

۹۹,۲۱۰,۰۰۰

Camera Type

PTZ

PTZ

PTZ

PTZ

PTZ

PTZ

Imaging Sensor

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

3MP(2048x1536/20FPS)

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.05Lux/F2

0.05Lux/F2

0.05Lux/F1.6

0.02Lux/F1/5

0.01Lux/F1.6

0.01Lux/F1.6

Lens

3.6-8.6mm Motorized

2.8-12mm Motorized

4.7-94mm Motorized

4.7-94mm Motorized

4.3-129mm Motorized

4.7-94mm Motorized

Optical Zoom

2x

4x

20x

20x

30x

20x

IR Range

-

-

100m

150m

-

50m

Body Type

-

Metal

Metal

Metal

Metal

-

IP Standard

-

IP66

IP66

IP66

IP66 & IK10

-

WDR

DWDR

No

DWDR

DWDR

DWDR

DWDR

WIFI

No

No

No

No

No

Built in WIFI

Power Supply

12VDC & POE(802.3at)

24v AC

12VDC & POE(802.3at)

24v AC & HI-POE

AC24V & POE(802.3at)

12VDC & POE(802.3at)

Other Features

16x Digital Zoom, Auto track, 3D DNR, ICR, BLC, built in mic

16x Digital Zoom, Auto Focus, 3D DNR, ICR, BLC

16x Digital Zoom, Auto Focus, 3DDNR, ICR, BLC, 1ch.audio

16x Digital Zoom, H.265+, 3DDNR, ICR, BLC, 1ch.audio

16x Digital Zoom, MICROSD, 3D DNR, H.264, BLC, 1ch.audio

16x Digital Zoom, 3D DNR, auto tracking BLC, sound support

69

70

71

72

73

74

Click for More
information

DS-2DE7230IW-AE

DS-2DE7220IW-AE

DS-2DE7184-AE

DS-2DE7320IW-AE

DS-2DE7330IW-AE

DS-2DE7420IW-AE



Price (Rials)	۱۵۶,۴۹۰,۰۰۰	۱۳۵,۲۹۰,۰۰۰	Call:88500020	۱۷۷,۱۹۰,۰۰۰	۱۸۳,۷۷۰,۰۰۰	۱۸۷,۶۰۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	2MP(1920x1080/20FPS)	2MP(1920x1080/20FPS)	3MP(2048x1536/20FPS)	3MP(2048x1536/20FPS)	4MP(2560x1440/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.05Lux/F1.6	0.05Lux/F1.6	0.01Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6	0.05Lux/F1.6
Lens	4.3-129mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.7-94mm Motorized	4.3-129mm Motorized	5.9-118mm Motorized
Optical Zoom	30x	20x	30x	20x	30x	20x
IR Range	150m	150m	100m	150m	150m	150m
Body Type	Metal	Metal	-	Metal	Metal	Metal
IP Standard	IP66	IP66	IP66	IP66	IP66	IP66
WDR	DWDR	DWDR	DWDR	No	No	No
WIFI	No	No	No	No	No	No
Power Supply	24v AC & HI-POE	24v AC & HI-POE	24v AC & HI-POE	12VDC & POE(802.3at)	12VDC & POE(802.3at)	24v AC & HI-POE
Other Features	16x Digital Zoom, 1.ch audio, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, 1ch.audio, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, 1ch.audio, 3D DNR, H.264, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, Auto Focus, 3D DNR, H.265+/H.265, BLC	12x Digital Zoom, EIS, Auto track,3D DNR, H.265+/H.265, BLC

75

76

77

[Click for More information](#)

DS-2DE7430IW-AE

DS-2DE7530IW-AE

DS-2PT3326IZ-DE3



Price (Rials)	٢٠٥,١٩٠,٠٠٠	٢٣٠,٨٨٠,٠٠٠	١٠٢,٨٠٠,٠٠٠
Camera Type	PTZ	PTZ	PTZ
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	4MP(2560x1440/30FPS)	5MP(2592x1944/30FPS)	2MP(1920x1080/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF
Min. Illustration	0.05Lux/F1.6	0.05Lux/F1.6	0.01Lux/F1.6
Lens	5.9-177mm Motorized	5.9-177mm Motorized	2.8-12mm
Optical Zoom	30x	30x	4x
IR Range	150m	150m	10m
Body Type	Metal	Metal	Aluminum alloy
IP Standard	IP66	IP66	IP66
WDR	DWDR	DWDR	DWDR
WIFI	No	No	No
Power Supply	24v AC & HI-POE	24v AC & HI-POE	12VDC & POE(802.3at)
Other Features	16x Digital Zoom, face detection, 3D DNR, H.265+/H.265, BLC	16x Digital Zoom, VCA, 3D DNR, H.265+/H.265, BLC, 1ch.audio	8x Digital Zoom, ICR, VCA, MICRO SD, HLC

برای کنترل موجودی در لیست قیمت با شماره زیر تماس بگیرید:

021-88500020

(10 خط)

78

79

80

81

82

83

Click for More
information

DS-7104NI-E1/M

DS-7604NI-E1

DS-7604NI-E1/4P

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7604NI-Q1



Price (Rials)

Call:88500020

۱۴,۶۷۰,۰۰۰

۲۰,۹۸۰,۰۰۰

۱۶,۵۰۰,۰۰۰

۲۳,۰۰۰,۰۰۰

۱۶,۵۰۰,۰۰۰

NVR Type

4 Ch NVR

4 Ch NVR

4 Ch POE NVR

4 Ch NVR

4 Ch POE NVR

4 Ch NVR

Input BandWidth

40Mbps

40Mbps

40Mbps

40Mbps

40Mbps

40Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

4Ch. : 1080P

4Ch. : 1080P

4Ch. : 1080P

4Ch. : 1080P
1Ch. : 4K4Ch. : 1080P
1Ch. : 4K4Ch. : 1080P
1Ch. : 4K

Video Output

1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI:1080P
1 Port VGA1 Port HDMI:1080P
1 Port VGA1 Port HDMI : 4K
1 Port VGA1 Port HDMI : 4K
1 Port VGA1 Port HDMI : 4k
1 Port VGA

POE Ports

-

-

4 POE Ports

-

4 POE Ports

-

SATA Interface

1 HDD up to 6TB

1 HDD up to 4TB

1 HDD up to 4TB

1 HDD up to 8TB

1 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.264 COMPR

H.265 COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1

H.265+ COMPR

H.265+ COMPR

H.265+ COMPR

84

85

86

[Click for More information](#)

DS-7604NI-Q1/4P

DS-7104NI-Q1/M

DS-7104NI-Q1/4P/M



Price (Rials)	۲۳,۰۳۴,۰۰۰	۱۰,۷۱۰,۰۰۰	۱۷,۷۰۰,۰۰۰
NVR Type	4 Ch POE NVR	4 Ch	4 Ch POE NVR
Input BandWidth	40Mbps	40Mbps	40Mbps
Output Bandwidth	80Mbps	60Mbps	60Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	8 Megapixel	4Ch. : 1080P 1Ch. : 6MP	2Ch. : 1080P 1Ch. : 4MP
Video Output	1 Port HDMI : 4K 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA
POE Ports	4 POE Ports	-	4 POE Ports
SATA Interface	1 HDD up to 8TB	1 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 1000M	1 RJ45 100M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U
Other Feathures	H.265+ COMPR	H.265+ COMPR	H.265+ COMPR

87

88

89

90

91

92

Click for More
information

DS-7108NI-E1

DS-7608NI-E2

DS-7608NI-E2/8P

DS-7608NI-K2

DS-7608NI-K2/8P

DS-7608NI-Q1



Price (Rials)

Call:88500020

۲۰,۵۴۰,۰۰۰

۳۳,۱۳۲,۰۰۰

۲۵,۱۵۰,۰۰۰

۳۹,۸۲۰,۰۰۰

۲۲,۸۴۹,۰۰۰

NVR Type

8 Ch POE NVR

8 Ch NVR

8 Ch POE NVR

8 Ch NVR

8 Ch POE NVR

8 Ch NVR

Input BandWidth

50Mbps

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

160Mbps

160Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

6Ch. : 720P
4Ch. : 1080P1Ch. : 4K
4Ch. : 1080P1Ch. : 4K
4Ch. : 1080P1Ch. : 4K
8Ch. : 1080P1Ch. : 4K
8Ch. : 1080P1Ch. : 4K
4Ch. : 1080P

Video Output

1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI : 1080P
1 Port VGA : 1080P1 Port HDMI : 1080P
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

-

8 POE Ports

-

8 POE Ports

-

SATA Interface

1 HDD up to 6TB

2 HDD up to 8TB

2 HDD up to 8TB

2 HDD up to 8TB

2 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 1000M

1 RJ45 100M

1 RJ45 100M

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Feathures

H.264 COMPR

H.264+ COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1H.265+ COMPR
Alarm I/O 4/1H.265+ COMPR
Alarm I/O 4/1

H.265+ COMPR

	93	94	95	96
Click for More information	DS-7608NI-Q1/8P	DS-7608NI-Q2	DS-7108NI-Q1/M	DS-7108NI-Q1/8P/M



Price (Rials)	۳۷,۰۶۰,۰۰۰	۲۵,۱۸۰,۰۰۰	۲۵,۱۸۰,۰۰۰	۲۴,۹۲۰,۰۰۰
NVR Type	8 Ch POE NVR	8 Ch NVR	8 Ch NVR	8 Ch NVR
Input BandWidth	80Mbps	80Mbps	60Mbps	60Mbps
Output Bandwidth	80Mbps	80Mbps	60Mbps	60Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	1Ch. : 4K 4Ch. : 1080P	6Ch. : 720P 4Ch. : 1080P	4Ch. : 1080P 1Ch. : 6MP	2Ch. : 1080P 1Ch. : 4MP
Video Output	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA : 1920p	1 Port HDMI : 1080p 1 Port VGA	1 Port HDMI : 1080p 1 Port VGA
POE Ports	8 POE Ports	-	-	8 POE Ports
SATA Interface	1 HDD up to 8TB	2 HDD up to 6TB	1 HDD up to 6TB	1 HDD up to 6TB
Network Interface	1 RJ45 100M	1 RJ45 1000M	1 RJ45 100M	1 RJ45 100M
Chassis	Standalone 1U	Standalone 1U	Standalone 1U	Standalone 1U
Other Feathures	H.265+ COMPR	H.265+ COMPR	H.265+ COMPR	H.265+ COMPR

97

98

99

100

101

102

Click for More
information

DS-7616NI-E2

DS-7616NI-E2/8P

DS-7616NI-E2/16P

DS-7716NI-E4

DS-7716NI-E4/16P

DS-7616NI-K2



Price (Rials)

۲۲,۶۳۰,۰۰۰

۳۴,۷۴۲,۰۰۰

۴۶,۴۹۰,۰۰۰

۴۹,۳۶۰,۰۰۰

۷۴,۰۸۰,۰۰۰

۲۷,۲۴۰,۰۰۰

NVR Type

16 Ch NVR

16 Ch POE NVR

16 Ch POE NVR

16 Ch NVR

16 Ch NVR

16 Ch NVR

Input BandWidth

160Mbps

160Mbps

160Mbps

80Mbps

80Mbps

160Mbps

Output Bandwidth

80Mbps

80Mbps

80Mbps

80Mbps

80Mbps

160Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

1Ch. : 4K
6Ch. : 1080P1Ch. : 4K
6Ch. : 1080P1Ch. : 4K
6Ch. : 1080P

6Ch. : 1080P

6Ch. : 1080P

8Ch. : 1080P
1Ch. : 4K

Video Output

1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI:1080P
1 Port VGA:1080P1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

-

8 POE Ports

16 POE Ports

-

16 POE Ports

-

SATA Interface

2 HDD up to 8TB

2 HDD up to 6TB

2 HDD up to 8TB

4 HDD up to 6TB

4 HDD up to 6TB

2 HDD up to 6TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

19" 1.5 Case

19" 1.5 Case

Standalone 1U

Other Features

H.264+ COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1H.264+ COMPR
Alarm I/O 4/1H.265+ COMPR
Alarm I/O 4/1

	103	104	105	106	107
Click for More information	DS-7616NI-K2/16P	DS-7716NI-K4	DS-7716NI-K4/16P	DS-7616NI-Q1	DS-7616NI-Q2/16P



Price (Rials)	۵۲,۸۰۰,۰۰۰	۶۱,۰۰۰,۰۰۰	۸۳,۴۹۰,۰۰۰	۲۳,۷۶۰,۰۰۰	۵۲,۸۰۰,۰۰۰
NVR Type	16 Ch NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR	16 Ch NVR
Input BandWidth	160Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	160Mbps	160Mbps	160Mbps	80Mbps	80Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	8Ch. : 1080P 1Ch. : 4K	8Ch. : 1080P 1Ch. : 4K	8Ch. : 1080P 1Ch. : 4K	1Ch. : 4K 4Ch. : 1080P	1Ch. : 4K 4Ch. : 1080P
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA : 1920P
POE Ports	16 POE Ports	-	16 POE Ports	-	16 POE Ports
SATA Interface	2 HDD up to 6TB	4 HDD up to 8TB	4 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 8TB
Network Interface	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	19" 1.5 Case	19" 1.5 Case	1U chassis	1U chassis
Other Feathures	H.265+ COMPR Alarm I/O 4/1	H.265+ COMPR Alarm I/O 4/1	H.265+ COMPR Alarm I/O 4/1	H.265+ COMPR	H.265+ COMPR

	108	109	110	111	112
Click for More information	DS-7732NI-E4	DS-7732NI-E4/16P	DS-7732NI-K4	DS-7732NI-K4/16P	DS-7600NI-E1/A



Price (Rials)	۶۴,۷۳۰,۰۰۰	۸۸,۴۷۹,۰۰۰	۷۶,۸۳۰,۰۰۰	۹۷,۷۳۰,۰۰۰	۶۹,۱۹۰,۰۰۰
NVR Type	32 Ch NVR	32 Ch NVR	32 Ch NVR	32 Ch POE NVR	
Input BandWidth	160Mbps	160Mbps	256Mbps	256Mbps	Advertising files import and preview,The output resolution of LCD is up to 1080P, Third party network cameras supported,Up to 8-ch synchronous playback at 720P resolution,Up to 8 network cameras can be connected,Smart search and smart playback 1TB HDD WD10JUCT pre-installed
Output Bandwidth	80Mbps	80Mbps	160Mbps	160Mbps	
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	
Decoding Capacity	6Ch. : 1080P 1Ch. : 4K	6Ch. : 1080P 1Ch. : 4K	8Ch. : 1080P 1Ch. : 4K	8Ch. : 1080P 1Ch. : 4K	
Video Output	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI:1080P 1 Port VGA:1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	
POE Ports	-	16 POE Ports	-	16 POE Ports	
SATA Interface	4 HDD up to 6TB	4 HDD up to 6TB	4 HDD up to 8TB	4 HDD up to 8TB	
Network Interface	2 RJ45 1000M	2 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	
Chassis	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	19" 1.5 Case	
Other Features	1 E-SATA Port H.264+ COMPR Alarm I/O 16/4	1 E-SATA Port H.264+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	H.265+ COMPR Alarm I/O 16/4	