

# HIKVISION

لیست قیمت رسمی بهار ۱۴۰۱

تارتن دژ آریانا

جشنواره بهار هایک ویژن

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

1

2

3

4

5

6

Click for More  
information

DS-2CD1023G0E-I

DS-2CD1023G0-IUF

DS-2CD1043G0-I

DS-2CD1053G0-I

DS-2CD1123G0E-I

DS-2CD1323G0-IUF



Price (Rials)

۱۷,۹۳۰,۰۰۰

۲۲,۲۵۰,۰۰۰

۲۵,۶۵۰,۰۰۰

۲۹,۳۳۰,۰۰۰

۲۰,۵۰۰,۰۰۰

۲۲,۲۵۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Dome

Dome

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

Resolution

2MP(1920x1080/30FPS)

2MP(1920x1080/30FPS)

4MP(2560x1440/20fps)

5MP (2560 × 1920/20fps)

2MP(1920x1080/30FPS)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F2.0

0.01Lux @ F2.0

0.01Lux @ F2.0

0.01Lux @ F1.2

0.028Lux @ F2.0

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

112.1°/90.2°

112.1°/90.2°

98°/78.7°

98°/75.3°

114.8°/86°

112.1°/90.2°

IR Range

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m (EXIR)

Up to 30m

Up to 30m (EXIR)

Body Type &amp; Standard

Plastic / IP67

Metal/Plastic / IP67

Plastic / IP67

Plastic / IP67

Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256G)

No

No

No

Yes (Up to 256G)

Microphone Support

No

Yes (Built in MIC)

No

No

No

Yes (Built in MIC)

WDR

DWDR

DWDR

DWDR

Yes (120db)

DWDR

DWDR

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, ROI, H.265+  
COMP

7

8

9

10

11

12

Click for More  
information

DS-2CD1143G0-I

DS-2CD2023G2-I

DS-2CD2027G2-L

DS-2CD2043G2-I

DS-2CD2047G2-L

DS-2CD2063G2-I



Price (Rials)

۲۸,۱۶۰,۰۰۰

۳۵,۱۳۰,۰۰۰

۳۷,۷۶۰,۰۰۰

۳۷,۷۶۰,۰۰۰

۴۳,۰۵۰,۰۰۰

۴۱,۶۲۰,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2560×1440/20fps)

2MP(1920×1080/25FPS)

2MP(1920×1080/25FPS)

4MP(2560×1440/30fps)

4MP(2560×1440/30fps)

6MP (3072 × 2048/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.028Lux @ F2

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

98°/78.7°

107°/87°

107°/87°

103°/84°

1097°/94°

107°/87°

IR Range

Up to 30m

Up to 40m (EXIR)

Up to 40m (Color Vu)

Up to 40m

Up to 40m (Color Vu)

Up to 40m

Body Type &amp; Standard

Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal/Plastic / IP67

SD Card Support

No

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Microphone Support

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

WDR

DWDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, VCA,  
H.265+ COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP

13

14

15

16

17

18

Click for More information

DS-2CD2083G2-I

DS-2CD2143G2-IU

DS-2CD2163G0-IU

DS-2CD2183G0-IS

DS-2CD2T43G2-2I

DS-2CD2T43G0-I5



Price (Rials)

۴۹,۵۱۰,۰۰۰

۴۰,۶۳۰,۰۰۰

۴۲,۵۲۰,۰۰۰

۴۸,۷۹۰,۰۰۰

۴۴,۰۲۰,۰۰۰

۴۶,۴۰۰,۰۰۰

Camera Type

Bullet

Dome

Dome

Dome

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/3" Prog. CMOS

1/2.9" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

8MP(3072×1728/20fps)

4MP(2688 × 1520/25fps)

6MP(3072 × 2048/20fps)

8MP(3840 × 2160/15fps)

4MP(2560×1440/25fps)

4MP(2560×1440/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005 Lux @ F1.6

0.028 Lux @ F2.0

0.01Lux @ F1.2

0.005Lux @ F1.6

0.01Lux @ F1.2

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4/6 mm Fixed

2.8/4/6 mm Fixed

Viewing Angle

107°/87°

103°/84°

97°/78°

102°/79°

103°/84°/52°

103°/83°/51°

IR Range

Up to 40m

Up to 30m

Up to 30m

Up to 30m

Up to 60m (EXIR)

Up to 50m (EXIR)

Body Type &amp; Standard

Metal/Plastic / IP67

Metal / IP67 &amp; IK10

Metal / IP66 &amp; IK10

Metal / IP67 &amp; IK10

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256 G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 256G)

Yes (Up to 128G)

Microphone Support

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (1.ch Audio Input)

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, HLC, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP3D DNR, BLC, ROI, H.265+  
COMP,PIR

19

20

21

22

23

24

Click for More  
information

DS-2CD2T43G0-I8

DS-2CD2T63G0-I8

DS-2CD2T83G0-I8

DS-2CD1623G0-I

DS-2CD1643G0-IZ

DS-2CD1743G0-IZ



Price (Rials)

۴۵,۸۵۰,۰۰۰

۵۰,۲۵۰,۰۰۰

۵۳,۱۱۰,۰۰۰

۴۱,۱۳۰,۰۰۰

۴۹,۸۸۰,۰۰۰

۵۳,۳۸۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Dome

Imaging Sensor

1/3" Prog. CMOS

1/2.9" Prog. CMOS

1/2.5" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

4MP(2688×1520/25fps)

6MP(3072×2048/20fps)

8MP(3840 × 2160/15fps)

2MP(1920 × 1080/30fps)

4MP(2560 × 1440/20fps)

4MP (2560x1440/20FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.01Lux @ F1.2

0.005Lux @ F1.6

0.018Lux @ F2

Lens

2.8/4/6 mm Fixed

2.8/4/6 mm Fixed

2.8/4 mm Fixed

2.8-12mm Varifocal

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

103°/83°/51°

97°/78°/60°

102°/79°

98°~34°

102°~31°

91.2°~28.3°

IR Range

Up to 80m (EXIR)

Up to 80m (EXIR)

Up to 80m (EXIR)

Up to 30m (EXIR)

Up to 50m (EXIR)

Up to 30m (EXIR)

Body Type &amp; Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

DWDR

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, HLC,H.265+  
COMP, ROI3D DNR, BLC, ROI, H.265+  
COMP,PIR3D DNR, BLC, ROI, H.265+  
COMP

3D DNR, BLC, H.265+ COMP

25

26

27

Click for More  
information

DS-2CD2643G2-IZS

DS-2CD2743G1-IZS

DS-2CD2443G0-IW



Price (Rials)	۷۳,۱۲۰,۰۰۰	۷۵,۳۹۰,۰۰۰	۳۷,۵۰۰,۰۰۰
Camera Type	Bullet	Dome	Cube
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS
Resolution	4MP(2688 × 1520/25fps)	4MP (2560x1440/20FPS)	4MP(2688x1520/30fps)
Network Standard	ONVIF	ONVIF	ONVIF
Min. Illustration	0.005Lux @ F1.6	0.01Lux @ F1.2	0.01Lux @ F1.2
Lens	2.8-12mm Motorized	2.8-12mm Motorized	2.8/4mm Fixed
Viewing Angle	95.8°~29.2°	104°~29°	98°/78°
IR Range	Up to 60m	Up to 30m	Up to 10m
Body Type & Standard	Metal / IP67,IK10	Metal / IP67,IK10	Plastic
SD Card Support	Yes (Up to 256G)	Yes (Up to 128G)	Yes (up to 128GB)
Microphone Support	Yes (1.ch Audio Input)	Yes (1.ch Audio Input)	Yes (Built-in Mic & Spkr)
WDR	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	Yes
Power Supply	12V DC or POE	12V DC or POE	12V DC
Other Features	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR

28

29

30

31

32

Click for More information

DS-2CD2955FWD-I

DS-2CD2955FWD-IS

DS-2DE4225IW-DE T5

DS-2DE4425IW-DE

DS-2DE4425IW-DE T5



Price (Rials)	97,350,000	100,470,000	125,920,000	147,070,000	147,070,000
Camera Type	Fisheye	Fisheye	PTZ	PTZ	PTZ
Imaging Sensor	1/2.5" Prog. CMOS	1/2.5" Prog. CMOS	1/2.8" Prog. CMOS	1/2.5" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	5MP(2560 × 1920/30FPS)	5MP(2560 × 1920/30FPS)	2MP(1920x1080/60FPS)	4MP(1920x1080/30FPS)	4MP(1920x1080/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux/F1.2	0.01Lux/F1.2	0.005Lux/F1.6	0.005Lux/F1.6	0.005Lux/F1.6
Lens	1.05mm	1.05mm	4.8-120mm Motorized	4.8-120mm Motorized	4.8-120mm Motorized
Viewing Angle	180°	180°	25x	25x	25x
IR Range	Up to 8 m	Up to 8 m	Up to 100m	Up to 100m	Up to 100m
Body Type & Standard	-	-	Metal/IP66	Metal/IP66	Metal/IP66
SD Card Support	Yes (Up to128G)	Yes (Up to128G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)
Microphone Support	No	Yes (1.ch Audio Input)	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No
Power Supply	12VDC & POE(802.3at)	12VDC & POE(802.3at)	24VAC & POE(802.3at)	24VAC & POE(802.3at)	24VAC & POE(802.3at)
Other Features	3D DNR, H.265+	3D DNR, H.265+	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, VCA, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR

33

34

35

36

Click for More  
information

DS-7104NI-Q1/M

DS-7604NI-K1

DS-7108NI-Q1/M

DS-7608NI-K1



Price (Rials)

۱۹,۴۷۰,۰۰۰

۳۵,۱۱۰,۰۰۰

۲۵,۶۰۰,۰۰۰

۳۸,۳۸۰,۰۰۰

NVR Type

4 Ch

4 Ch

8 Ch

8 Ch

Input BandWidth

40Mbps

40Mbps

60Mbps

80Mbps

Output Bandwidth

60Mbps

80Mbps

60Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 8Mp

Upto 4Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 1080p  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P

POE Ports

-

-

-

-

SATA Interface

1 HDD up to 6TB

1 HDD up to 8TB

1 HDD up to 6TB

1 HDD up to 8TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP  
Alarm I/O 4/1



37

38

39

Click for More  
information

DS-7616NI-Q1

DS-7616NI-K2

DS-7616NI-Q2/16P



Price (Rials)

۴۵,۷۲۰,۰۰۰

۵۴,۷۷۰,۰۰۰

۸۸,۰۴۰,۰۰۰

NVR Type

16 Ch

16 Ch

16 Ch / 16 POE

Input BandWidth

160Mbps

160Mbps

160Mbps

Output Bandwidth

80Mbps

160Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4k  
1 Port VGA1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4k  
1 Port VGA : 1920P

POE Ports

-

-

16 POE Ports

SATA Interface

1 HDD up to 8TB

2 HDD up to 6TB

2 HDD up to 8TB

Network Interface

1 RJ45 1000M

1 RJ45 1000M

1 RJ45 1000M

Chassis

1U chassis

Standalone 1U

1U chassis

Other Features

H.265+ COMPR

H.265+ COMPR  
Alarm I/O 4/1

H.265+ COMPR

40

41

42

43

Click for More  
information

DS-7732NI-K4

DS-7732NI-K4/16P

DS-7732NI-Q4

DS-7732NI-Q4/16P



Price (Rials)

۱۲۳,۷۹۰,۰۰۰

۱۹۲,۸۰۰,۰۰۰

۱۱۳,۸۷۰,۰۰۰

۱۶۲,۶۲۰,۰۰۰

NVR Type

32 Ch

32 Ch / 16 POE

32 Ch

32 Ch / 16 POE

Input BandWidth

256Mbps

256Mbps

200Mbps

200Mbps

Output Bandwidth

160Mbps

160Mbps

128Mbps

128Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI : 4K  
1 Port VGA : 1080P1 Port HDMI:1080P  
1 Port VGA:1080P1 Port HDMI:1080P  
1 Port VGA:1080P

POE Ports

-

16 POE Ports

-

16 POE Ports

SATA Interface

4 HDD up to 8TB

4 HDD up to 8TB

4 HDD up to 8TB

4 HDD up to 8TB

Network Interface

2 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

Chassis

19" 1.5 Case

19" 1.5 Case

19" Case

19" Case

Other Features

H.265+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4H.265+ COMPR  
Alarm I/O 16/4