

HIKVISION

لیست قیمت رسمی مهر ماه ۱۴۰۲

تارتن دژ آریانا

جهت اطلاع از تخفیف جشنواره هر محصول تماس بگیرید:

۰۲۱-۸۸۵۰۰۰۲۰



نمایندگی مرکزی محصولات هایک ویژن

	1	2	3	4	5	6
Click for More information	DS-2CD1023G0E-I(2.8mm)	DS-2CD1023G0-IUF	DS-2CD1043G0-I(4mm)	DS-2CD1053G0-I	DS-2CD1057G0-L	DS-2CD1123G0E-I



Price (Rials)	۲۶,۹۴۰,۰۰۰	۴۰,۷۷۰,۰۰۰	۳۵,۱۶۰,۰۰۰	۵۱,۹۴۰,۰۰۰	۵۸,۸۲۰,۰۰۰	۲۶,۳۶۰,۰۰۰
Camera Type	Bullet	Bullet	Bullet	Bullet	Bullet	Dome
Imaging Sensor	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.8" Prog. CMOS
Resolution	2MP(1920x1080/30FPS)	2MP(1920x1080/30FPS)	4MP(2560x1440/20fps)	4MP(2560x1440/20fps)	5MP (2560 × 1920/20fps)	2MP(1920x1080/30FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.01Lux @ F1.2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F1.2
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed
Viewing Angle	112.1°/90.2°	112.1°/90.2°	78.7°	98°	95°/76°	114.8°/86°
IR Range	Up to 30m	Up to 30m (EXIR)	Up to 30m	Up to 30m	Up to 30m (Color Vu)	Up to 30m
Body Type & Standard	Plastic / IP67	Metal/Plastic / IP67	Plastic / IP67	Plastic / IP67	Metal / IP67	Plastic / IP67
SD Card Support	No	Yes (Up to 256G)	No	No	Yes (Up to 256G)	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	DWDR	DWDR	DWDR	Yes (120db)	DWDR
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, ROI, H.265+ COMP,PIR	3D DNR, BLC, HLC, ROI, H.265+ COMP	3D DNR, BLC, H.265+ COMP

	7	8	9	10	11	12
Click for More information	DS-2CD1143G0-I	DS-2CD1143G0-IUF	DS-2CD1153G0-I(4mm)	DS-2CD1323G0E-I	DS-2CD1347G0-L	DS-2CD1353G0-I (2.8mm)



Price (Rials)	۴۱,۷۸۰,۰۰۰	۵۵,۹۶۰,۰۰۰	۵۴,۵۴۰,۰۰۰	۲۹,۵۹۰,۰۰۰	۸۱,۶۵۰,۰۰۰	۵۷,۰۰۰,۰۰۰
Camera Type	Dome	Dome	Dome	Dome	Dome	Dome
Imaging Sensor	1/3" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS	1/2.7" Prog. CMOS	1/3" Prog. CMOS	1/2.7" Prog. CMOS
Resolution	4MP(2560x1440/20fps)	4MP(2560x1440/20fps)	5MP(2560x1920/15FPS)	2MP(1920x1080/25FPS)	4MP(2560x1440/20fps)	5MP(2560x1920/20FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.028Lux @ F2	0.01Lux @ F2.0	0.01Lux @ F2.0	0.01Lux @ F2.0	0.001Lux @ F1.0	0.01Lux @ F2.0
Lens	2.8/4 mm Fixed	2.8/4 mm Fixed	4 mm Fixed	2.8/4 mm Fixed	2.8/4 mm Fixed	2.8 mm Fixed
Viewing Angle	98°/78.7°	98°/78.7°	75.3°	105°/81°	96.5°/75.8°	98.0°
IR Range	Up to 30m	Up to 30m (Color Vu)	Up to 30m	Up to 30m (EXIR)	Up to 30m (Color Vu)	Up to 30m (EXIR)
Body Type & Standard	Plastic / IP67	Plastic / IP67/ IK10	Plastic / IP67/ IK10	Metal/Plastic / IP67	Metal/Plastic / IP67	Metal/Plastic / IP67
SD Card Support	No	Yes (Up to 256 G)	No	No	No	No
Microphone Support	No	Yes (Built in MIC)	No	No	No	No
WDR	DWDR	Yes (120db)	Yes (120db)	DWDR	No	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE	12V DC or POE
Other Features	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, ROI, VCA, H.265+ COMP	3D DNR, BLC, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP	3D DNR, BLC, ROI, H.265+ COMP

13

14

15

16

17

18

Click for More
information

DS-2CD1357G0-L

DS-2CD2021G1-I (2.8mm)

DS-2CD2023G2-I

DS-2CD2025FHWD-I

DS-2CD2027G2-L (2.8mm)

DS-2CD2043G2-I (2.8mm)



Price (Rials)

۵۸,۷۹۰,۰۰۰

۴۹,۹۸۰,۰۰۰

۵۹,۹۴۰,۰۰۰

۶۸,۵۳۰,۰۰۰

۷۱,۰۴۰,۰۰۰

۶۶,۴۶۰,۰۰۰

Camera Type

Dome

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/2.7" Prog. CMOS

1/2.7" Prog. CMOS

1/2.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.7" Prog. CMOS

1/3" Prog. CMOS

Resolution

5MP(2560x1920/20FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

2MP(1920x1080/25FPS)

4MP(2560x1440/30fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.001Lux @ F1.0

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.2

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

Viewing Angle

95°/76°

111.6°/91.5°

107°/87°

108°/86.4°

107°

103°

IR Range

Up to 30m (Color Vu)

Up to 30m (EXIR)

Up to 40m

Up to 30m

Up to 40m (Color Vu)

Up to 40m

Body Type & Standard

Metal/Plastic / IP67

Metal/Plastic / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

No

Yes (Up to 256 G)

No

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, ROI, H.265+
COMP

3D DNR, BLC, H.265+ COMP

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP

19

20

21

22

23

24

Click for More
information

DS-2CD2043G2-IU(2.8mm)

DS-2CD2046G2-I

DS-2CD2047G2-L

DS-2CD2063G2-I

DS-2CD2066G2-I

DS-2CD2083G2-I



Price (Rials)

۷۹,۱۱۰,۰۰۰

۷۰,۷۶۰,۰۰۰

۷۷,۷۳۰,۰۰۰

۷۲,۸۰۰,۰۰۰

۷۸,۳۹۰,۰۰۰

۷۷,۷۱۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2560×1440/30fps)

4MP(2688×1520/30fps)

4MP(2560×1440/30fps)

6MP(3200×1800/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

0.003Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

103°

103°/83°

112°/95°

105°/78°

105°/78°

107°/87°

IR Range

Up to 40m

Up to 40m

Up to 40m (Color Vu)

Up to 40m

Up to 40m

Up to 40m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 256 G)

Yes (Up to 512 G)

Yes (Up to 512 G)

Yes (Up to 512 G)

Microphone Support

Yes (Built in MIC)

No

No

No

No

No

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP

25

26

27

28

29

30

Click for More
information

DS-2CD2085G1-I

DS-2CD2086G2-I

DS-2CD2087G2-LU (2.8mm)

DS-2CD2123G2-IU

DS-2CD2126G2-ISU(2.8mm)

DS-2CD2143G2-IU



Price (Rials)

117,160,000

98,810,000

156,550,000

61,350,000

81,540,000

66,890,000

Camera Type

Bullet

Bullet

Bullet

Dome

Dome

Dome

Imaging Sensor

1/1.2" Prog. CMOS

1/1.8" Prog. CMOS

1/1.2" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/3" Prog. CMOS

Resolution

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

8MP(3072×1728/20fps)

4MP(2688 × 1520/25fps)

2MP(1920×1080/25FPS)

4MP(2688 × 1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.008Lux @ F1.2

0.003Lux @ F1.6

0.0005Lux @ F1.0

0.005 Lux @ F1.6

0.002 Lux @ F1.4

0.005 Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

Viewing Angle

102°/78°

111°/87°

102°

107°/87°

107°

103°/84°

IR Range

Up to 30m

Up to 40m

Up to 40m (ColorVu)

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

SD Card Support

Yes (Up to 128 G)

Yes (Up to 256 G)

Yes (Up to 256 G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, HLC, H.265+
COMP

31

32

33

34

35

36

Click for More
information

DS-2CD2147G2

DS-2CD2163G2-IU

DS-2CD2166G2-ISU(2.8mm)

DS-2CD2183G2-IU

DS-2CD2185FWD-I

DS-2CD2H25FWD-IZS



Price (Rials)

۸۵,۰۰۰,۰۰۰

۷۰,۷۸۰,۰۰۰

۸۳,۴۸۰,۰۰۰

۷۴,۲۸۰,۰۰۰

۱۰۸,۴۶۰,۰۰۰

۱۳۸,۸۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Dome

Dome

Imaging Sensor

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.8" Prog. CMOS

1/2.5" Prog. CMOS

1/2.8" Prog. CMOS

Resolution

4MP(2688 × 1520/25fps)

6MP(3200 × 1800/25fps)

6MP(3200 × 1800/25fps)

8MP(3840 × 2160/25fps)

8MP(3840 × 2160/25fps)

2MP(1920x1080/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005 Lux @ F1.0

0.005 Lux @ F1.6

0.003 Lux @ F1.6

0.005 Lux @ F1.6

0.01 Lux @ F1.2

0.005Lux @ F1.2

Lens

2.8 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8-12mm Motorized

Viewing Angle

112°

107°/87°

105°/78°

107°/87°

107°/87°

105°~35°

IR Range

Up to 30m (Color Vu)

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Up to 30m

Body Type & Standard

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP67 & IK10

Metal / IP66/IK10

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 128G)

Yes (Up to 128 G)

Microphone Support

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

Yes (Built in MIC)

No

Yes (1.ch Audio Input)

WDR

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, HLC,H.265+
COMP3D DNR, BLC, ROI, HLC, H.265+
COMP, DarkFighter

37

38

39

40

41

42

Click for More
information

DS-2CD2327G2-L(2.8)

DS-2CD2347G2-L(2.8mm)

DS-2CD2346G2-IU

DS-2CD2347G2-LU(2.8mm)

DS-2CD2T43G2-2I(2.8)

DS-2CD2T43G2-2I(4mm)



Price (Rials)

۸۱,۱۱۰,۰۰۰

۷۸,۹۱۰,۰۰۰

۷۵,۱۳۰,۰۰۰

۸۹,۷۶۰,۰۰۰

۶۶,۹۷۰,۰۰۰

۶۶,۹۷۰,۰۰۰

Camera Type

Dome

Dome

Dome

Dome

Bullet

Bullet

Imaging Sensor

1/2.8" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

Resolution

2MP(1920x1080/25FPS)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

4MP(2688 × 1520/25fps)

4MP(2688x1520/25fps)

4MP(2688x1520/25fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.0005 Lux @ F1.0

0.0005 Lux @ F1.0

0.003 Lux @ F1.4

0.0005 Lux @ F1.0

0.005Lux @ F1.6

0.005Lux @ F1.6

Lens

2.8 mm Fixed

2.8 mm Fixed

2.8/4 mm Fixed

2.8 mm Fixed

2.8 mm Fixed

4 mm Fixed

Viewing Angle

107°

112°

103°/83°

112°

103°

84°

IR Range

Up to 30m

Up to 30m (Color Vu)

Up to 30m

Up to 30m (Color Vu)

Up to 60m (EXIR)

Up to 60m (EXIR)

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (Built in MIC)

Yes (Built in MIC)

No

No

WDR

Yes (120db)

Yes (130db)

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP, DarkFighter3D DNR, BLC, HLC, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP

43

44

45

46

47

48

Click for More
information

DS-2CD2T43G2-4I(4mm)

DS-2CD2T47G-L

DS-2CD2T63G2-4I

DS-2CD2T66G2-4I

DS-2CD2T83G2-4I

DS-2CD2T85G1-I8



Price (Rials)

۷۲,۳۸۰,۰۰۰

۹۵,۵۸۰,۰۰۰

۸۰,۸۶۰,۰۰۰

۹۳,۱۸۰,۰۰۰

۹۳,۹۰۰,۰۰۰

۱۳۴,۷۳۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Bullet

Imaging Sensor

1/3" Prog. CMOS

1/1.8" Prog. CMOS

1/2.8" Prog. CMOS

1/2.4" Prog. CMOS

1/2.5" Prog. CMOS

1/2.5" Prog. CMOS

Resolution

4MP(2688×1520/25fps)

4MP(2688×1520/25fps)

6MP(3200×1800/25fps)

6MP(3200×1800/25fps)

8MP(3840 × 2160/15fps)

8MP(3840 × 2160/15fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.0005Lux @ F1.0

0.005Lux @ F1.6

0.003Lux @ F1.6

0.005Lux @ F1.2

0.01Lux @ F1.2

Lens

4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

2.8/4 mm Fixed

Viewing Angle

84°

112°/95°

107°/87°

105°/87°

102°/79°

102°/79°

IR Range

Up to 80m (EXIR)

Up to 60m (Color Vu)

Up to 80m (EXIR)

Up to 60m (EXIR)

Up to 80m (EXIR)

Up to 80m

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 256G)

Yes (Up to 128G)

Microphone Support

No

No

No

No

No

No

WDR

Yes (120db)

Yes (130db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, HLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, HLC, H.265+
COMP, ROI3D DNR, BLC, HLC, H.265+
COMP, ROI3D DNR, BLC, HLC, H.265+
COMP, ROI

49

50

51

52

53

54

Click for More
information

DS-2CD2T86G2-4I

DS-2CD1643G0-IZ

DS-2CD2643G2-IZS

DS-2CD2683G2-IZS

DS-2CD2686G2-IZS

DS-2CD1743G0-IZ



Price (Rials)

۱۲۰,۱۵۰,۰۰۰

۸۱,۳۵۰,۰۰۰

۱۲۴,۷۱۰,۰۰۰

۱۳۹,۳۰۰,۰۰۰

۱۷۸,۳۷۰,۰۰۰

۹۱,۳۴۰,۰۰۰

Camera Type

Bullet

Bullet

Bullet

Bullet

Bullet

Dome

Imaging Sensor

1/1.8" Prog. CMOS

1/3" Prog. CMOS

1/3" Prog. CMOS

1/2.8" Prog. CMOS

1/2" Prog. CMOS

1/3" Prog. CMOS

Resolution

8MP(3840 × 2160/25fps)

4MP(2560 × 1440/20fps)

4MP(2688 × 1520/25fps)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2560x1440/20fps)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.003Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.005Lux @ F1.6

0.008Lux @ F1.2

0.005Lux @ F1.6

Lens

2.8/4 mm Fixed

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

Viewing Angle

111°/87°

102°~31°

95.8°~29.2°

108°~30°

112°~46°

91.2°~28.3°

IR Range

Up to 80m (EXIR)

Up to 50m (EXIR)

Up to 60m

Up to 60m

Up to 50m

Up to 30m (EXIR)

Body Type & Standard

Metal / IP67

Metal / IP67

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67

SD Card Support

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 256G)

Yes (Up to 512G)

Yes (Up to 128G)

Yes (Up to 256G)

Microphone Support

No

No

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

No

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, HLC, H.265+
COMP, ROI3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP3D DNR, BLC, ROI, H.265+
COMP-3D DNR, BLC, ROI, H.265+
COMP- DarkFighter

3D DNR, BLC, H.265+ COMP

55

56

57

58

Click for More
information

DS-2CD2743G2-IZS

DS-2CD2783G2-IZS

DS-2CD2785G1-IZS

DS-2CD2443G0-IW(W)



Price (Rials)

۱۴۹,۰۰۰,۰۰۰

۱۳۷,۴۷۰,۰۰۰

۱۵۰,۳۲۰,۰۰۰

۶۱,۱۳۰,۰۰۰

Camera Type

Dome

Dome

Dome

Cube

Imaging Sensor

1/3" Prog. CMOS

1/2" Prog. CMOS

1/2" Prog. CMOS

1/3" Prog. CMOS

Resolution

4MP (2560x1440/20FPS)

8MP(3840 × 2160/20fps)

8MP(3840 × 2160/20fps)

4MP (2688x1520/25FPS)

Network Standard

ONVIF

ONVIF

ONVIF

ONVIF

Min. Illustration

0.005Lux @ F1.6

0.008Lux @ F1.2

0.008Lux @ F1.2

0.01Lux @ F1.2

Lens

2.8-12mm Motorized

2.8-12mm Motorized

2.8-12mm Motorized

2.8/4 mm Fixed

Viewing Angle

104°~29°

112°~46°

112°~46°

98°/78

IR Range

Up to 40m

Up to 30m

Up to 30m

Up to 10m

Body Type & Standard

Metal / IP67,IK10

Metal / IP67,IK10

Metal / IP67,IK10

Plastic

SD Card Support

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Yes (Up to 128G)

Microphone Support

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (1.ch Audio Input)

Yes (Built in MIC)

WDR

Yes (120db)

Yes (120db)

Yes (120db)

Yes (120db)

WIFI

No

No

No

No

Power Supply

12V DC or POE

12V DC or POE

12V DC or POE

12V DC or POE

Other Features

3D DNR, BLC, H.265+ COMP,
Deep Learning3D DNR, BLC, ROI, H.265+
COMP- DarkFighter3D DNR, BLC, ROI, H.265+
COMP- DarkFighter3D DNR, BLC, HLC, H.265+
COMP, PIR

	59	60	61	62	63	64
Click for More information	DS-2SE4C225MWG-E	DS-2DE4225IW-DE T5	DS-2SE4C425MWG-E	DS-2DE4425IW-DE T5	DS-2DE7A432IW-AEB(T5)	DS-2CD2955FWD-LS
						
Price (Rials)	۲۸۱,۸۱۰,۰۰۰	۲۱۴,۵۹۰,۰۰۰	۳۲۰,۵۶۰,۰۰۰	۲۵۲,۱۵۰,۰۰۰	۴۱۲,۱۷۰,۰۰۰	۱۰۲,۹۶۰,۰۰۰
Camera Type	PTZ	PTZ	PTZ	PTZ	PTZ	Fisheye
Imaging Sensor	1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/3" Prog. CMOS(Bullet) 1/2.8" Prog. CMOS	1/2.8" Prog. CMOS	1/1.8" Prog. CMOS	1/2.5" Prog. CMOS
Resolution	2MP(1920x1080/60FPS)	2MP(1920x1080/60FPS)	4MP(2560x1440/60FPS)	4MP(2560 × 1440/30FPS)	4MP(2560 × 1440/30FPS)	5MP(2560 × 1920/25FPS)
Network Standard	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF	ONVIF
Min. Illustration	0.0005Lux/F1.0 0.005Lux/F1.6	0.005Lux/F1.6	0.0005Lux/F1.0 0.005Lux/F1.6	0.005Lux/F1.6	0.005Lux/F1.5	0.01Lux/F1.2
Lens	2.8mm (Bullet) 4.8-120mm Motorized	4.8-120mm Motorized	2.8mm (Bullet) 4.8-120mm Motorized	4.8-120mm Motorized	5.9-188.8mm Motorized	1.05mm
Viewing Angle	106°(Bullet) 25x (PTZ)	25x	96.1°(Bullet) 25x (PTZ)	25x	32x	180°
IR Range	Up to 30m(Bullet) Up to 100m	Up to 100m	Up to 30m(Bullet) Up to 100m	Up to 100m	Up to 200m	Up to 8 m
Body Type & Standard	Metal/IP66	Metal/IP66	Metal/IP66	Metal/IP66	Metal/IP66, IK10	Metal
SD Card Support	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 256G)	Yes (Up to 128G)
Microphone Support	No	No	No	No	No	No
WDR	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)	Yes (120db)
WIFI	No	No	No	No	No	No
Power Supply	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	12 VDC & POE(802.3at)	24 VAC & Hi-POE	12VDC & POE(802.3at)
Other Features	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR	16x Digital Zoom, H.265+, HLC, BLC, 3D DNR, DarkFighter	3D DNR, H.265+, Anti-flicker

65

66

67

68

69

70

Click for More
information

DS-7104NI-Q1/M

DS-7108NI-Q1/M

DS-7604NI-K1

DS-7604NI-K1/4P

DS-7608NI-Q1

DS-7608NI-K1



Price (Rials)

۴۲,۳۸۰,۰۰۰

۴۹,۳۸۰,۰۰۰

۶۱,۵۶۰,۰۰۰

۸۲,۷۴۰,۰۰۰

۵۸,۳۰۰,۰۰۰

۶۸,۳۴۰,۰۰۰

NVR Type

4 Ch

8 Ch

4 Ch

4 Ch / 4 POE

8 Ch

8 Ch

Input BandWidth

40Mbps

60Mbps

40Mbps

40Mbps

80Mbps

80Mbps

Output Bandwidth

60Mbps

60Mbps

80Mbps

80Mbps

80Mbps

80Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

Decoding Capacity

Upto 4Mp

Upto 4Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Video Output

1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 1080p
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4k
1 Port VGA1 Port HDMI : 4K
1 Port VGA : 1080P

POE Ports

-

-

-

4 POE Ports

-

-

SATA Interface

1 HDD up to 6TB

1 HDD up to 6TB

1 HDD up to 8TB

1 HDD up to 8TB

2 HDD up to 8TB

1 HDD up to 8TB

Network Interface

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

1 RJ45 100M

Chassis

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Standalone 1U

Other Features

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP

H.265+ COMP
Alarm I/O 4/1

	71	72	73	74	75	76
Click for More information	DS-7608NI-K2	DS-7608NI-K1/8P	DS-7616NI-Q2	DS-7716NI-Q4/16P	DS-7616NI-K1	DS-7616NI-K2



Price (Rials)	۷۱,۲۰۰,۰۰۰	۱۲۶,۱۹۰,۰۰۰	۸۹,۸۱۰,۰۰۰	۲۵۵,۱۴۰,۰۰۰	۸۵,۸۰۰,۰۰۰	۸۲,۹۷۰,۰۰۰
NVR Type	8 Ch	8 Ch / 8 POE	16 Ch	16 Ch / 16 POE	16 Ch	16 Ch
Input BandWidth	80Mbps	80Mbps	160Mbps	160Mbps	160Mbps	160Mbps
Output Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	80Mbps	160Mbps
Audio Input/Output	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out	1Ch. In/ 1Ch. Out
Decoding Capacity	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp	Upto 8Mp
Video Output	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4k 1 Port VGA	1 Port HDMI : 4K 1 Port VGA : 1080P	1 Port HDMI : 4K 1 Port VGA : 1080P
POE Ports	-	8 POE Ports	-	16 POE Ports	-	-
SATA Interface	1 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 8TB	4 HDD up to 8TB	1 HDD up to 8TB	2 HDD up to 10TB
Network Interface	1 RJ45 100M	1 RJ45 100M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M	1 RJ45 1000M
Chassis	Standalone 1U	Standalone 1U	1U	1.5U	Standalone 1U	1U
Other Features	H.265+ COMP Alarm I/O 4/1	H.265+ COMP Alarm I/O 4/1	H.265+ COMP	H.265+ COMP Alarm I/O 16/4	H.265+ COMP	H.265+ COMP

77

78

79

80

81

82

Click for More
information

DS-7616NI-K2/16P

DS-7716NI-K4

DS-7732NI-K4

DS-7732NI-K4/16P

IDS-7732NXI-I4/8S

DS-9632NI-I8



Price (Rials)

۱۶۲,۳۴۰,۰۰۰

۲۱۱,۱۹۰,۰۰۰

۲۱۰,۴۵۰,۰۰۰

۳۳۴,۳۱۰,۰۰۰

۷۱۹,۱۶۰,۰۰۰

۷۱۰,۰۰۰,۰۰۰

NVR Type

16 Ch / 16 POE

16 Ch

32 Ch

32 Ch / 16 POE

32 Ch

32 Ch

Input BandWidth

160Mbps

160Mbps

256Mbps

256Mbps

320Mbps

320Mbps

Output Bandwidth

160Mbps

160Mbps

160Mbps

160Mbps

256Mbps

256Mbps

Audio Input/Output

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 1Ch. Out

1Ch. In/ 2Ch. Out

Decoding Capacity

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 8Mp

Upto 12Mp

Video Output

1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P1 Port HDMI : 4K
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P

POE Ports

16 POE Ports

-

-

16 POE Ports

-

-

SATA Interface

2 HDD up to 10TB

4 HDD up to 10TB

4 HDD up to 8TB

4 HDD up to 8TB

4 HDD up to 10TB

8 HDD up to 10TB

Network Interface

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

1 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

Chassis

1U

1.5 U

19" 1.5 Case

19" 1.5 Case

19" 1.5 Case

19" 1.5 Case

Other Features

H.265+ COMPR

H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/4H.265+ COMPR
Alarm I/O 16/8 - Esata 1-
DeepinMindH.265+ COMPR
Alarm I/O 16/4, RAID

83

84

85

Click for More
information

IDS-9632NXI-I8/4F

DS-9632NXI-I8/S

IDS-9664NXI-I8/S



Price (Rials)

۳,۲۱۳,۸۹۰,۰۰۰

۷۳۹,۰۲۰,۰۰۰

۹۶۸,۶۳۰,۰۰۰

NVR Type

32 Ch

32 Ch

64 Ch

Input BandWidth

320Mbps

320Mbps

320Mbps

Output Bandwidth

256Mbps

256Mbps

256Mbps

Audio Input/Output

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

1Ch. In/ 2Ch. Out

Decoding Capacity

Upto 12Mp

Upto 12Mp

Upto 12Mp

Video Output

2 Port HDMI : 4K/1080P
2 Port VGA : 1080P2 Port HDMI : 4K/1080P
2 Port VGA : 1080P2 Port HDMI : 4K/1080P
1 Port VGA : 1080P

POE Ports

-

-

-

SATA Interface

8 HDD up to 10TB

8 HDD up to 10TB

8 HDD up to 10TB

Network Interface

2 RJ45 1000M

2 RJ45 1000M

2 RJ45 1000M

Chassis

2U

2U

2U

Other Features

H.265+ COMPR
Alarm I/O 16/8, RAID,
DeepinMind- Esata 1H.265+ COMPR
Alarm I/O 16/8, RAID,
DeepinMind- Esata 1H.265+ COMPR
Alarm I/O 16/8, RAID,
DeepinMind