

DS-PWA64-Kit1-WE



- DS-PWA64-L-WE x 1
- DS-PKF1-WE x 2
- DS-PS1-E-WE (Blue) x 1
- DS-PDP15P-EG2-WE x 2
- DS-PDMC-EG2-WE x 1

▪ Specification

Software features	
Tag	32
Area	16
Zones	64 (up to 48 PIRCAMs)
Installer	1
User	30
Admin	1
Voice Prompt	Supported
Loudspeaker built in	Supported
Memory Log stored	5000
Programming tools	Hik-Connect/Hik-Partner Pro/Web Portal/IVMS4200/Convergence Cloud
Firmware upgrade	APP/Web Portal
Arm modes	Away/Stay
Automatic Arm/Disarm Timers	Supported
Forced Arming with Open Zones	Supported
Diagnostics via the APP or Web	Supported
ARC protocol	SIA DC09(SIA level 2, Contact ID), ISUP, ISAPI (SDK) Hik-IP Receiver & Hik-IP Receiver Pro (Sur-Gard & Ademco 685) Supports video verification and remote control
User APP for operating	Supported
Installer APP for programming	Supported
Web server for maintenance (offline configuration)	Supported
Hardware features	
RS232 output	Supported
SIM slot	Single
RF transmission	
RF Frequency	868 Mhz
Wireless Security	Frequency Hoping 128 AES Encryption
GPRS on board	Supported
Electrical characteristics	
Power supply	Built in power supply
Battery type	Built in on board Battery Li
Battery life span	Up to 12 hours at normal temperature (The battery working time can be significantly reduced at low temperatures)
Wireless transmission	
Wired network	Supported
Wi-Fi Standard	Supported
Display	
LEDs Status	Arm/Disarm, Alarm, Tamper, Fault, Cloud, Power
General	
Operation temperature	-10 °C to +55 °C
Shell material	Plastic

Dimension(WxHxD)	170.0 mm (6.7") x 170.0 (6.7") mm x 38.6 mm (1.5")
Weight	557.5 g (19.7 oz)
Color	White
Device management	
Keyfob	32
Wireless sounder	4 (2 internal+2 External)
Keypad	8 (Including Tag reader)
Wireless Repeater	2
Multi Transmitter	4
PIR Cam	Supported

▪ **Available Model**

DS-PWA64-Kit1-WE

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

